



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NA

MPI2007 license: 021

Test sponsor: Scali, Inc.

Tested by: Scali, Inc.

Test date: Sep-2007

Hardware Availability: Sep-2007

Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

- Ranks
- 104.milc
- 107.leslie3d
- 113.GemsFDTD
- 115.fds4
- 121.pop2
- 122.tachyon
- 126.lammps
- 127.wrf2
- 128.GAPgeofem
- 129.tera_tf
- 130.socor
- 132.zeusmp2

Results Table

Benchmark	Base								Peak					
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	NA	NA	NA	NA	NA	NA							
107.leslie3d	64	NA	NA	NA	NA	NA	NA							
113.GemsFDTD	64	NA	NA	NA	NA	NA	NA							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = No Run
SPECmpiM_base2007 = NA

MPI2007 license: 021
Test sponsor: Scali, Inc.
Tested by: Scali, Inc.

Test date: Sep-2007
Hardware Availability: Sep-2007
Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
115.fds4	64	NA	NA	NA	NA	NA	NA							
121.pop2	64	NA	NA	NA	NA	NA	NA							
122.tachyon	64	NA	NA	NA	NA	NA	NA							
126.lammps	64	NA	NA	NA	NA	NA	NA							
127.wrf2	64	NA	NA	NA	NA	NA	NA							
128.GAPgeofem	64	NA	NA	NA	NA	NA	NA							
129.tera_tf	64	NA	NA	NA	NA	NA	NA							
130.socorro	64	NA	NA	NA	NA	NA	NA							
132.zeusmp2	64	NA	NA	NA	NA	NA	NA							
137.lu	64	NA	NA	NA	NA	NA	NA							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System: Homogenous
Compute Node: 48DMC
Interconnects: mpiComm, GBEthernet
File Server: 4100
Total Compute Nodes: 8
Total Chips: 16
Total Cores: 64
Total Memory: 128 GB
Base Rank Run: 64
Minimum Peak Ranks: --
Maximum Peak Ranks: --

Software Summary

C Compiler: QLogic PathScale C Compiler 3.0
C++ Compiler: QLogic PathScale C++ Compiler 3.0
Fortran Compiler: QLogic PathScale Fortran Compiler 3.0
Base Pointers: 64-bit
Peak Pointers: Not Applicable
MPI Library: Scali MPI Connect 5.5
Other MPI Info: OFED 1.2.5 ibverbs
Pre-processors: No
Other Software: None



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = No Run
SPECmpiM_base2007 = NA

MPI2007 license: 021
Test sponsor: Scali, Inc.
Tested by: Scali, Inc.

Test date: Sep-2007
Hardware Availability: Sep-2007
Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

Node Description: H8DMU

Hardware		Software	
Number of nodes:	8	Adapter:	Ethernet controller: nVidia Corporation MCP55 Ethernet
Uses of the node:	compute	Adapter Driver:	OS default
Vendor:	SuperMicro	Adapter Firmware:	Unknown
Model:	H8DMU+	Adapter:	Mellanox ConnectX DDR, board id MT_04A0110002
CPU Name:	AMD Opteron CPU 2350	Adapter Driver:	OFED 1.2.5
CPU(s) orderable:	1 or 2 chips	Adapter Firmware:	2.2.000
Chips enabled:	2	Operating System:	CentOS release 4.5 (Final), 2.6.9-55.0.2.ELsmp
Cores enabled:	8	Local File System:	ext3
Cores per chip:	4	Shared File System:	NFS
Threads per core:	1	System State:	Multi-user
CPU Characteristics:	Quad-Core AMD Opteron Processor 2350 (Barcelona)	Other Software:	None
CPU MHz:	2000		
Primary Cache:	64 KB I + 64 KB D on chip per core		
Secondary Cache:	512 KB I+D on chip per core		
L3 Cache:	2 MB I+D on chip per chip		
Other Cache:	None		
Memory:	16 GB (8 x 2 GB DDR2 667 Micron)		
Disk Subsystem:	400GB Seagate SATA, 7200RPM		
Other Hardware:	None		
Adapter:	Ethernet controller: nVidia Corporation MCP55 Ethernet		
Number of Adapters:	2		
Slot Type:	PCIe x8		
Data Rate:	10 Gbps Ethernet		
Ports Used:	1		
Interconnect Type:	Gigabit Ethernet		
Adapter:	Mellanox ConnectX DDR, board id MT_04A0110002		
Number of Adapters:	1		
Slot Type:	PCIe x8		
Data Rate:	InfiniBand 4x DDR		
Ports Used:	1		
Interconnect Type:	Infiniband		



SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = No Run
SPECmpiM_base2007 = NA

MPI2007 license: 021
Test sponsor: Scali, Inc.
Tested by: Scali, Inc.

Test date: Sep-2007
Hardware Availability: Sep-2007
Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

Node Description: X4100

Hardware		Software	
Number of nodes:	1	Adapter:	Intel Corporation 82546EB Gigabit Ethernet Controller
Uses of the node:	fileserver	Adapter Driver:	OS default
Vendor:	Sun Microsystems, Inc.	Adapter Firmware:	Unknown
Model:	Sun Fire X4100	Operating System:	CentOS release 4.5 (Final), 2.6.9-55.0.2.ELsmp
CPU Name:	AMD Opteron 285	Local File System:	ext3
CPU(s) orderable:	1-2 chip	Shared File System:	NFS
Chips enabled:	2	System State:	Multi-user
Cores enabled:	4	Other Software:	None
Cores per chip:	2		
Threads per core:	1		
CPU Characteristics:	Dual Core AMD Opteron Processor 285		
CPU MHz:	2600		
Primary Cache:	64 KB I + 64 KB D on chip per core		
Secondary Cache:	1 MB I+D on chip per chip		
L3 Cache:	None		
Other Cache:	None		
Memory:	8 GB (8 x 1 GB DDR2/667 ECC registered DIMMs)		
Disk Subsystem:	2x SAS 10K RPM mirrored		
Other Hardware:	None		
Adapter:	Intel Corporation 82546EB Gigabit Ethernet Controller		
Number of Adapters:	4		
Slot Type:	PCIe x8		
Data Rate:	10 Gbps Ethernet		
Ports Used:	1		
Interconnect Type:	Gigabit Ethernet		

Interconnect Description: mpiComm

Hardware		Software	
Vendor:	Voltaire		
Model:	Voltaire 9024D 24 ports DDR switch		
Switch Model:	9024D		
Number of Switches:	1		
Number of Ports:	24		
Data Rate:	InfiniBand 4x DDR		

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = No Run
SPECmpiM_base2007 = NA

MPI2007 license: 021
Test sponsor: Scali, Inc.
Tested by: Scali, Inc.

Test date: Sep-2007
Hardware Availability: Sep-2007
Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

Interconnect Description: mpiCollan

Firmware: Unknown
Topology: single switch (star)
Primary Use: MPI traffic

Interconnect Description: GBEthernet

	Hardware	Software
Vendor:	Nortel	
Model:	Nortel Networks Baystack 5510 Gigabit Ethernet switch	
Switch Model:	5510	
Number of Switches:	1	
Number of Ports:	24	
Data Rate:	1 Gbps Ethernet	
Firmware:	fw: 1.0.0.16, sw: v3.0.1.00	
Topology:	Single Switch	
Primary Use:	file system traffic	

Submit Notes

Scali MPI Connect wrapper has been used to submit the jobs. Description of switches:
-m: launch 8 processes per node.
-s: switch as method to connect to nodes.
-stdin none: do not connect the processes' STDIN to anything.
-q: quiet mode, no output from launcher.
-machinefile: file selecting the hosts to run on.

General Notes

Scali, Inc has executed the benchmark on AMD Development Center. We are grateful for the support from AMD and in particular Joshua Mora and Brian Taylor in order to finalize the submissions.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = No Run
SPECmpiM_base2007 = NA

MPI2007 license: 021
Test sponsor: Scali, Inc.
Tested by: Scali, Inc.

Test date: Sep-2007
Hardware Availability: Sep-2007
Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

Base Compiler Invocation

C benchmarks:
/opt/scali/bin/mpicc -ccl pathcc
C++ benchmarks:
126.lammps: /opt/scali/bin/mpicc -ccl pathcc
Fortran benchmarks:
/opt/scali/bin/mpif77 -ccl pathf90
Benchmarks using both Fortran and C:
/opt/scali/bin/mpicc -ccl pathcc /opt/scali/bin/mpif77 -ccl pathf90

Base Portability Flags

104.milc: -DSPEC_MPI_LP64
115.fds4: -DSPEC_MPI_C_TRAILING_DOUBLE_UNDERSCORE -DSPEC_MPI_LP64
121.pop2: -DSPEC_MPI_C_TRAILING_DOUBLE_UNDERSCORE -DSPEC_MPI_LP64
122.tachyon: -DSPEC_MPI_LP64
127.wrf2: -DF2CSTYLE -DSPEC_MPI_DOUBLE_UNDERSCORE -DSPEC_MPI_LINUX
-DSPEC_MPI_LP64
128.CarlProfem: -DSPEC_MPI_LP64
130.socorro: -fno-second-underscore -DSPEC_MPI_LP64
132.zeusmp2: -DSPEC_MPI_LP64

Base Optimization Flags

C benchmarks:
-march=core -Ofast -OPT:malloc_alg=1
C++ benchmarks:
126.lammps: -march=core -O3 -OPT:Ofast -CG:local_fwd_sched=on
Fortran benchmarks:
-march=core -O3 -OPT:Ofast -OPT:malloc_alg=1 -LANG:copyinout=off

Continued on next page



SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Colfax International
Barcelona Cluster

SPECmpiM_peak2007 = No Run
SPECmpiM_base2007 = NA

MPI2007 license: 021
Test sponsor: Scali, Inc.
Tested by: Scali, Inc.

Test date: Sep-2007
Hardware Availability: Sep-2007
Software Availability: Aug-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the processor vendor reported that the processor would not meet the SPEC HPG requirements for continued availability.

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

`-march=core -Ofast -OPT:malloc_alg=1 -O3 -OPT:ofast
-LANG:copyinout=off`

Base Other Flags

C benchmarks:

`-IPA:max_jobs=4`

C++ benchmarks:

`126.lammps: -IPA:max_jobs=4`

Fortran benchmarks:

`-IPA:max_jobs=4`

Benchmarks using both Fortran and C:

`-IPA:max_jobs=4`

The flags file that was used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/MPI2007_flags.20071107.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/mpi2007/flags/MPI2007_flags.20071107.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.0.
Report generated on Tue Jul 22 13:33:07 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 7 November 2007.