



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Linux Networx

LS-1,
Scali MPI Connect 5.6.1,
PathScale 3.0 compilers

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 021
Test sponsor: Scali, Inc
Tested by: Scali, Inc

Test date: Feb-2008
Hardware Availability: Sep-2007
Software Availability: Feb-2008

Ranks
104.milc
107.leslie3d
113.GemsFDTD
115.fds4
121.pop2
122.tachyon
126.lammps
127.wrf2
128.GAPgeofem
129.tera_tf
130.socorro
132.zeusmp2
137.lu

Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	128	NC	NC	NC	NC	NC	NC							
107.leslie3d	128	NC	NC	NC	NC	NC	NC							
113.GemsFDTD	128	NC	NC	NC	NC	NC	NC							
115.fds4	128	NC	NC	NC	NC	NC	NC							
121.pop2	128	NC	NC	NC	NC	NC	NC							
122.tachyon	128	NC	NC	NC	NC	NC	NC							
126.lammps	128	NC	NC	NC	NC	NC	NC							
127.wrf2	128	NC	NC	NC	NC	NC	NC							
128.GAPgeofem	128	NC	NC	NC	NC	NC	NC							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Linux Networx

LS-1,
Scali MPI Connect 5.6.1,
PathScale 3.0 compilers

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 021

Test sponsor: Scali, Inc

Tested by: Scali, Inc

Test date: Feb-2008

Hardware Availability: Sep-2007

Software Availability: Feb-2008

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
129.tera_tf	128	NC	NC	NC	NC	NC	NC							
130.socorro	128	NC	NC	NC	NC	NC	NC							
132.zeusmp2	128	NC	NC	NC	NC	NC	NC							
137.lu	128	NC	NC	NC	NC	NC	NC							

Results appear in the order in which they were run. Bold underlined text indicates median measurement.

Hardware Summary

Type of System: Homogenous
 Compute Node: Linux Networx LS-1
 Interconnect: InfiniBand
 File Server Node: Linux Networx LS1 I/O Nodes
 Total Compute Nodes: 32
 Total Chips: 64
 Total Cores: 128
 Total Threads: 128
 Total Memory: 256 GB
 Base Ranks Run: 128
 Minimum Peak Ranks: --
 Maximum Peak Ranks: --

Software Summary

C Compiler: PathScale C Compiler 3.0
 C++ Compiler: PathScale C++ Compiler 3.0
 Fortran Compiler: PathScale Fortran Compiler 3.0
 Pointer Size: 64-bit
 Precision: Not Applicable
 MPI Library: Scali MPI Connect 5.6.1-58818
 Other MPI Info: IB Gold VAPI
 Pre-processors: None
 Other Software: None

Node Description: Linux Networx LS-1

Hardware

Number of nodes: 32
 Uses of the node: compute
 Vendor: Linux Networx, Inc
 Model: LS-1
 CPU Name: Intel Xeon 5160
 CPU(s) orderable: 1-2 chips
 Chips enabled: 2
 Cores enabled: 2
 Cores per chip: 2
 Threads per core: 1
 CPU FSB: 1333 Mhz FSB
 CPU MHz: 3000
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (8 x 1GB DIMMs 667 MHz)
 Disk Subsystem: 250GB SAS hard drive
 Other Hardware: None
 Adapter: Mellanox MHGA28-XTC
 PCI-Express DDR InfiniBand HCA

Software

Adapter: Mellanox MHGA28-XTC
 Adapter Driver: PCI-Express DDR InfiniBand HCA
 Adapter Firmware: IBGD 1.8.2
 Operating System: SLES9 SP3
 Local File System: Not applicable
 Shared File System: GPFS
 System State: multi-user
 Other Software: None

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Linux Networkx

SPECmpiM_peak2007 = Not Run

LS-1,
Scali MPI Connect 5.6.1,
PathScale 3.0 compilers

SPECmpiM_base2007 = Not Run

MPI2007 license: 021

Test date: Feb-2008

Test sponsor: Scali, Inc

Hardware Availability: Sep-2007

Tested by: Scali, Inc

Software Availability: Feb-2008

Node Description: Linux Networkx LS-1

Number of Adapters: 1
Slot Type: PCIe x8
Data Rate: InfiniBand 4x DDR
Ports Used: 1
Interconnect Type: Infiniband

Node Description: Linux Networkx LS1 I/O Nodes

Hardware

Number of nodes: 8
Uses of the node: file server
Vendor: Linux Networkx, Inc.
Model: LS1
CPU Name: Intel Xeon 5150
CPU(s) orderable: 1-2 chips
Chips enabled: 2
Cores enabled: 4
Cores per chip: 2
Threads per core: 1
CPU Characteristics: 1333 Mhz FSB
CPU MHz: 2660
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 4 GB (4 x 1GB DIMMs 667 MHz)
Disk Subsystem: 18 TB SAN inter-connected by FC4
Other Hardware: None
Adapter: Mellanox MHGA28-XTC
PCI-X DDR InfiniBand HCA

Number of Adapters: 1
Slot Type: PCIe x8
Data Rate: InfiniBand 4x DDR
Ports Used: 1
Interconnect Type: InfiniBand

Software

Adapter Driver: Mellanox MHGA28-XTC
PCI-X DDR InfiniBand HCA
IBGD 1.8.2
Adapter Firmware: 5.2.0
Operating System: SLES9 SP3
Local File System: Not applicable
Shared File System: GPFS
System State: multi-user
Other Software: None

Interconnect Description: InfiniBand

Hardware

Vendor: QLogic
Model: QLogic Silverstorm 9120 Fabric Director
Switch Model: 9120
Number of Switches: 1
Number of Ports: 144

Software

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Linux Networx

LS-1,
Scali MPI Connect 5.6.1,
PathScale 3.0 compilers

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 021
Test sponsor: Scali, Inc
Tested by: Scali, Inc

Test date: Feb-2008
Hardware Availability: Sep-2007
Software Availability: Feb-2008

Interconnect Description: InfiniBand

Data Rate: InfiniBand 4x SDR and InfiniBand 4x DDR
Firmware: 4.1.1.11
Topology: Single switch (star)
Primary Use: MPI and filesystem traffic

General Notes

The following approved srcalts are used
tera_tf - fixbuffer
wrf2 - fixcalling

Base Compiler Invocation

C benchmarks:
/opt/scali/bin/mpicc -ccl pathcc
C++ benchmarks:
126.lammps: /opt/scali/bin/mpicc -ccl pathCC
Fortran benchmarks:
/opt/scali/bin/mpif77 -ccl pathf90
Benchmarks using both Fortran and C:
/opt/scali/bin/mpicc -ccl pathcc /opt/scali/bin/mpif77 -ccl pathf90

Base Portability Flags

104.milc: -DSPEC_MPI_LP64
111.fds4: -DSPEC_MPI_LC_TRAILING_DOUBLE_UNDERSCORE -DSPEC_MPI_LP64
121.pcr2: -DSPEC_MPI_DOUBLE_UNDERSCORE -DSPEC_MPI_LP64
122.tachyon: -DSPEC_MPI_LP64
127.milc: -DF2CSTYLE -DSPEC_MPI_DOUBLE_UNDERSCORE -DSPEC_MPI_LINUX -DSPEC_MPI_LP64
128.CAPgeofem: -DSPEC_MPI_LP64
130.socorro: -fno-second-underscore -DSPEC_MPI_LP64
132.zetmp2: -DSPEC_MPI_LP64

Base Optimization Flags

C benchmarks:
-march=core -O3 -OPT:Ofast

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Linux Networx

LS-1,
Scali MPI Connect 5.6.1,
PathScale 3.0 compilers

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 021
Test sponsor: Scali, Inc
Tested by: Scali, Inc

Test date: Feb-2008
Hardware Availability: Sep-2007
Software Availability: Feb-2008

Base Optimization Flags (Continued)

C++ benchmarks:

126.lammps: -march=core -O3 -OPT:Ofast -CG:local_fwd_scheduling

Fortran benchmarks:

-march=core -O3 -OPT:Ofast -LANG:copyinout=off

Benchmarks using both Fortran and C:

-march=core -O3 -OPT:Ofast -LANG:copyinout=off

The flags files that were used to format the result can be browsed at

http://www.spec.org/mpi2007/flags/MPI2007_flags.20080611.html
http://www.spec.org/mpi2007/flags/MPI2007_flags.0.html

You can also download the XML flags sources by saving the following links:

http://www.spec.org/mpi2007/flags/MPI2007_flags.20080611.xml
http://www.spec.org/mpi2007/flags/MPI2007_flags.0.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.0.
Report generated on Tue Jul 22 13:33:40 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 31 March 2008.