



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5472, 3.00 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Mar-2008

Software Availability: Apr-2008

Ranks
104.milc
107.leslie3d
113.GemsFDTD
115.fds4
121.pop2
122.tachyon
126.lammps
127.wrf2
128.GAPgeofem
129.tera_tf
130.socorro
132.zeusmp2
137.lu

Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	NC	NC	NC	NC									
107.leslie3d	64	NC	NC	NC	NC									
113.GemsFDTD	64	NC	NC	NC	NC									
115.fds4	64	NC	NC	NC	NC									
121.pop2	64	NC	NC	NC	NC									
122.tachyon	64	NC	NC	NC	NC									
126.lammps	64	NC	NC	NC	NC									
127.wrf2	64	NC	NC	NC	NC									
128.GAPgeofem	64	NC	NC	NC	NC									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5472, 3.00 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Mar-2008

Software Availability: Apr-2008

Results Table (Continued)

Benchmark	Base						Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
129.tera_tf	64	NC	NC	NC	NC									
130.socorro	64	NC	NC	NC	NC									
132.zeusmp2	64	NC	NC	NC	NC									
137.lu	64	NC	NC	NC	NC									

Results appear in the order in which they were run. Bold underlined text indicates median measurement.

Hardware Summary

Type of System: Homogeneous
 Compute Node: SGI Altix ICE 8200EX Compute Node
 Interconnects: InfiniBand (MPI)
 InfiniBand (I/O)
 File Server Node: SGI InfiniteStorage NAS/SAN
 Total Compute Nodes: 8
 Total Chips: 16
 Total Cores: 64
 Total Threads: 64
 Total Memory: 128 GB
 Base Ranks Run: 64
 Minimum Peak Ranks: --
 Maximum Peak Ranks: --

Software Summary

Compiler: Intel C Compiler for Linux
 Version 10.1, Build 20080312
 C++ Compiler: Intel C++ Compiler for Linux
 Version 10.1, Build 20080312
 Fortran Compiler: Intel Fortran Compiler for Linux
 Version 10.1, Build 20080312
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 MPI Library: Intel MPI 3.1.038
 Other MPI Info: OFED 1.3
 Pre-processors: None
 Other Software: None

Node Description: SGI Altix ICE 8200EX Compute Node

Hardware

Number of nodes: 8
 Uses of the node: compute
 Vendor: SGI
 Model: SGI Altix ICE 8200EX (Intel Xeon X5472, 3.00 GHz)
 CPU Name: Intel Xeon X5472
 CPU(s) orderable: 1-2 chips
 Chips enabled: 16
 Cores enabled: 64
 Cores per chip: 4
 Threads per core: 1
 CPU Characteristics: Quad Core, 3.0GHz
 CPU MHz: 3000
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8*2GB PC2-6400 CL5-5-5 FB-DIMMs)
 Disk Subsystem: None
 Other Hardware: None
 Adapter: Mellanox MT26418 ConnectX IB DDR
 (PCIe x8 Gen2 5 GT/s)

Software

Adapter: Mellanox MT26418 ConnectX IB DDR
 (PCIe x8 Gen2 5 GT/s)
 Adapter Driver: OFED-1.3
 Adapter Firmware: 2.3.0
 Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1
 Kernel 2.6.16.46-0.12-smp
 Local File System: NFSv3
 Shared File System: NFSv3 IPoIB
 System State: Multi-user, run level 3
 Other Software: SGI ProPack 5 for Linux Service Pack 5

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5472, 3.00 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = Not Run

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: May-2008
Hardware Availability: Mar-2008
Software Availability: Apr-2008

Node Description: SGI Altix ICE 8200EX Compute Node

Number of Adapters: 1
Slot Type: PCIe x8 Gen2
Data Rate: InfiniBand 4x DDR
Ports Used: 2
Interconnect Type: InfiniBand

Node Description: SGI InfiniteStorage Node/SAN

Hardware

Number of nodes: 1
Uses of the node: fileserver
Vendor: SGI
Model: SGI Altix 450 Density System (Itanium 2 Processor 9030 1.6GHz/8MB)
CPU Name: Dual-Core Intel Itanium 2 930
CPU(s) orderable: 1-38 chips
Chips enabled: 2
Cores enabled: 4
Cores per chip: 2
Threads per core: 1
CPU Characteristics: 533 MHz FSB
CPU MHz: 1594
Primary Cache: 16 KB I + 16 KB D on chip per core
Secondary Cache: 1 MB I + 256 KB D on chip per core
L3 Cache: 4 MB I+D on chip per core
Other Cache: None
Memory: 24 GB (6*4GB DDR2-400 DIMMS)
Disk Subsystem: 16 TB SATA
32 x 500 GB SATA (Seagate Barracuda 7200 rpm)
Other Hardware: None
Adapter: Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)

Number of Adapters: 2
Slot Type: PCIe x8 Gen1
Data Rate: InfiniBand 4x DDR
Ports Used: 2
Interconnect Type: InfiniBand

Software

Adapter Driver: Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)
Adapter Firmware: OFED-1.3
Operating System: 5.2.0
SUSE Linux Enterprise Server 10 (ia64) SP1
Kernel 2.6.16.54-0.2.5-default
Local File System: xfs
Shared File System: --
System State: Multi-user, run level 3
Other Software: SGI ProPack 5 for Linux Service Pack 5

Interconnect Description: InfiniBand (MPI)

Hardware

Vendor: Mellanox Technologies
Model: MT26418 ConnectX
Switch Model: Mellanox MT47396 InfiniScale III
Number of Switches: 32

Software

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5472, 3.00 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Mar-2008

Software Availability: Apr-2008

Interconnect Description: InfiniBand (MPI)

Number of Ports: 24
Data Rate: InfiniBand 4x DDR
Firmware: 2020001
Topology: Hypercube
Primary Use: MPI traffic

Interconnect Description: InfiniBand (I/O)

	Hardware	Software
Vendor:	Mellanox Technologies	
Model:	MT26418 ConnectX	
Switch Model:	Mellanox MT47396 InfiniScale-III	
Number of Switches:	32	
Number of Ports:	24	
Data Rate:	InfiniBand 4x DDR	
Firmware:	2020001	
Topology:	Hypercube	
Primary Use:	I/O traffic	

General Notes

Required alternate sources:
129.tera_tf: fixbuff

Base Compiler Invocation

C benchmarks:
mpicc

C++ benchmarks:

mpicpc

Fortran benchmarks:
mpiifort

Benchmarks using both Fortran and C:
mpicc mpiifort



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5472, 3.00 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Mar-2008

Software Availability: Apr-2008

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX

Base Optimization Flags

C benchmarks:

-O3 -ipo -xT -no-prec-div

C++ benchmarks:

126.lammps: -O3 -ipo -xT -no-prec-div -ansi-alias

Fortran benchmarks:

-O3 -ipo -xT -no-prec-div

Benchmarks using both Fortran and C:

-O3 -ipo -xT -no-prec-div

The flags file that was used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.0.
Report generated on Tue Jul 22 13:34:04 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 18 June 2008.