



# SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

[SPECmpIM\\_peak2007 = Not Run](#)

ThinkSystem SR665  
(AMD EPYC 7H12, 2.6 GHz)

[SPECmpIM\\_base2007 = 34.1](#)

MPI2007 license: 28


Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020



## Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	128	73.3	21.3	73.5	21.3	<b>73.4</b>	<b>21.3</b>									
107.leslie3d	128	237	22.0	<u>237</u>	<u>22.0</u>	238	21.9									
113.GemsFDTD	128	185	34.1	180	35.0	<u>182</u>	<u>34.7</u>									
115.fds4	128	63.3	30.8	64.3	30.4	<u>64.1</u>	<u>30.4</u>									
121.pop2	128	132	31.3	135	30.5	<u>133</u>	<u>31.2</u>									
122.tachyon	128	<u>75.5</u>	<u>37.0</u>	169877	0.0000490	75.4	37.1									
126.lammps	128	102	28.5	103	28.4	<u>103</u>	<u>28.4</u>									
127.wrf2	128	140	55.6	138	56.4	<u>139</u>	<u>56.3</u>									
128.GAPgeomfem	128	<u>59.3</u>	<u>34.8</u>	58.9	35.0	60.1	34.3									
129.tera_tf	128	81.2	34.1	91.0	30.4	<u>85.9</u>	<u>32.2</u>									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

[SPECmpIM\\_peak2007 = Not Run](#)

ThinkSystem SR665  
(AMD EPYC 7H12, 2.6 GHz)

[SPECmpIM\\_base2007 = 34.1](#)

MPI2007 license: 28

Test date: Jan-2020

Test sponsor: Lenovo Global Technology

Hardware Availability: Jun-2020

Tested by: Lenovo Global Technology

Software Availability: Jun-2020

## Results Table (Continued)

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	128	68.4	55.8	66.7	57.3	<b>66.9</b>	<b>57.1</b>									
132.zeusmp2	128	<b>94.0</b>	<b>33.0</b>	94.3	32.9	94.0	33.0									
137.lu	128	86.2	42.7	<b>85.8</b>	<b>42.8</b>	85.7	42.9									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

### Hardware Summary

Type of System: Homogeneous  
Compute Node: ThinkSystem SR665  
File Server Node: NFS  
Total Compute Nodes: 1  
Total Chips: 2  
Total Cores: 128  
Total Threads: 128  
Total Memory: 1 TB  
Base Ranks Run: 128  
Minimum Peak Ranks: --  
Maximum Peak Ranks: --

### Software Summary

C Compiler: Intel C Compiler 20.0 for Linux Version 19.1.0.166 Build 20191121  
C++ Compiler: Intel C++ Compiler 20.0 for Linux Version 19.1.0.166 Build 20191121  
Fortran Compiler: Intel Fortran Compiler for Linux Version 19.1.0.166 Build 20191121  
Base Pointers: 64-bit  
Peak Pointers: Not Applicable  
MPI Library: MPICH MPI Library Version 3.3.2  
Other MPI Info: None  
Pre-processors: No  
Other Software: None

## Node Description: ThinkSystem SR665

### Hardware

Number of nodes: 1  
Uses of the node: compute  
Vendor: Lenovo Global Technology  
Model: SR665  
CPU Name: AMD EPYC 7H12  
CPU(s) orderable: 1-2 chips  
Chips enabled: 2  
Cores enabled: 128  
Cores per chip: 64  
Threads per core: 1  
CPU Characteristics: None  
CPU MHz: 2600  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 512 KB I+D on chip per core  
L3 Cache: 256 MB I+D on chip per chip  
16 MB shared / 4 cores  
Other Cache: None  
Memory: 1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)  
Disk Subsystem: 1 x 480 GB SATA 2.5" SSD  
Other Hardware: None  
Adapter: Mellanox ConnectX-6 HDR Infiniband  
Number of Adapters: 1  
Slot Type: PCI-Express 4.0 x16

### Software

Adapter: Mellanox ConnectX-6 HDR Infiniband 4.7-1.0.0.1.2  
Adapter Driver: 20.25.2006  
Adapter Firmware: Red Hat Enterprise Linux Server release 8.1, 4.18.0-147.el8.x86\_64  
Operating System: xfs  
Local File System: None  
Shared File System: Multi-user, run level 3  
System State: Other Software: None

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

ThinkSystem SR665  
(AMD EPYC 7H12, 2.6 GHz)

[SPECmpIM\\_peak2007 = Not Run](#)

SPECmpIM\_base2007 = 34.1

**MPI2007 license:** 28

**Test date:** Jan-2020

**Test sponsor:** Lenovo Global Technology

**Hardware Availability:** Jun-2020

**Tested by:** Lenovo Global Technology

**Software Availability:** Jun-2020

### Node Description: ThinkSystem SR665

Data Rate: 200 Gbs/s  
Ports Used: 1  
Interconnect Type: Mellanox ConnectX-6 HDR Infiniband Adapter

### Node Description: NFS

#### Hardware

Number of nodes: 1  
Uses of the node: Fileserver  
Vendor: Lenovo Global Technology  
Model: ThinkSystem SR665  
CPU Name: AMD EPYC 7H12 CPU  
CPU(s) orderable: 1-2 chips  
Chips enabled: 2  
Cores enabled: 128  
Cores per chip: 64  
Threads per core: 1  
CPU Characteristics: None  
CPU MHz: 2600  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 512 KB I+D on chip per core  
L3 Cache: 256 MB I+D on chip per chip  
16 MB shared / 4 cores  
Other Cache: None  
Memory: 1 TB (16 x 64 GB 2Rx4 PC4-3200AA-R)  
Disk Subsystem: 1 x 480 GB SATA 2.5" SSD  
Other Hardware:  
Adapter: Mellanox ConnectX-6 HDR Infiniband  
Number of Adapters: 1  
Slot Type: PCI-Express 4.0 x16  
Data Rate: 200 Gb/s  
Ports Used: 1  
Interconnect Type: Mellanox ConnectX-6 HDR Infiniband

#### Software

Adapter: Mellanox ConnectX-6 HDR Infiniband  
Adapter Driver: 4.7-1.0.0.1.2  
Adapter Firmware: 20.25.2006  
Operating System: Red Hat Enterprise Linux Server release 8.1  
Local File System: None  
Shared File System: NFS  
System State: Multi-User, run level 3  
Other Software: None

### Submit Notes

The config file option 'submit' was used.

### General Notes

**MPI startup command:**

mpiexec command was used to start MPI jobs.

**RAM configuration:**

Compute nodes have 1 x 32 GB RDIMM on each memory channel.

Add "idle=poll" into grub

**BIOS settings:**

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

ThinkSystem SR665  
(AMD EPYC 7H12, 2.6 GHz)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = 34.1**

**MPI2007 license:** 28

**Test date:** Jan-2020

**Test sponsor:** Lenovo Global Technology

**Hardware Availability:** Jun-2020

**Tested by:** Lenovo Global Technology

**Software Availability:** Jun-2020

## General Notes (Continued)

Operating Mode : Maximum Performance Mode

Hyper-Threading Technology (SMT): Enabled

NPS4

Yes: The test sponsor attests, as of date of publication,  
that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,

that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication,  
that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

## Base Compiler Invocation

C benchmarks:

/opt/mpich/m332\_I201\_H47\_R81/bin/mpicc

C++ benchmarks:

126.lammps: /opt/mpich/m332\_I201\_H47\_R81/bin/mpicxx

Fortran benchmarks:

/opt/mpich/m332\_I201\_H47\_R81/bin/mpif90

Benchmarks using both Fortran and C:

/opt/mpich/m332\_I201\_H47\_R81/bin/mpicc

/opt/mpich/m332\_I201\_H47\_R81/bin/mpif90

## Base Portability Flags

121.pop2: -DSPEC\_MPI\_CASE\_FLAG

126.lammps: -DMPICH\_IGNORE\_CXX\_SEEK

127.wrf2: -DSPEC\_MPI\_CASE\_FLAG -DSPEC\_MPI\_LINUX

130.socorro: -assume nostd\_intent\_in

## Base Optimization Flags

C benchmarks:

-O3 -march=core-avx2 -no-prec-div -ipo

C++ benchmarks:

126.lammps: -O3 -march=core-avx2 -no-prec-div -ipo

Fortran benchmarks:

-O3 -march=core-avx2 -no-prec-div -ipo

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

ThinkSystem SR665  
(AMD EPYC 7H12, 2.6 GHz)

**SPECmpiM\_peak2007 = Not Run**

**SPECmpiM\_base2007 = 34.1**

**MPI2007 license:** 28

**Test date:** Jan-2020

**Test sponsor:** Lenovo Global Technology

**Hardware Availability:** Jun-2020

**Tested by:** Lenovo Global Technology

**Software Availability:** Jun-2020

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-O3 -march=core-avx2 -no-prec-div -ipo

The flags file that was used to format this result can be browsed at

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel121\\_flags.20200506.01.html](http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.01.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel121\\_flags.20200506.01.xml](http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20200506.01.xml)

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v2.0.1.

Report generated on Wed May 6 11:57:38 2020 by SPEC MPI2007 PS/PDF formatter v1463.  
Originally published on 6 May 2020.