



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 575 (2200 MHz, 8 CPU)

SPECompMpeak2001 = 40560

SPECompMbase2001 = 33521

SPEC license #HPG0005 | Tested by: IBM | Test site: Austin, TX | Test date: Dec-2005 | Hardware AvailFeb-2006 | Software AvailFeb-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	140	42983	121	49722	
312.swim_m	6000	163	36765	120	50178	
314.mgrid_m	7300	363	20127	167	43720	
316.applu_m	4000	81.8	48878	66.3	60328	
318.galgel_m	5100	117	43440	98.8	51625	
320.quake_m	2600	96.1	27041	80.7	32227	
324.apsi_m	3400	108	31511	97.7	34818	
326.gafort_m	8700	239	36468	214	40611	
328.fma3d_m	4600	265	17387	251	18310	
330.art_m	6400	76.6	83521	77.9	82188	
332.ammp_m	7000	355	19702	334	20979	

Hardware

CPU: POWER5+
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 8 cores, 8 chips, 1 core/chip (SMT on)
 CPU(s) orderable: 8,16
 Primary Cache: 64KBI+32KBD (on chip)/core
 Secondary Cache: 1920KB unified, shared (on chip)/chip
 L3 Cache: 36MB unified (off-chip)/DCM, 8 DCMs/SUT
 Other Cache: None
 Memory: 64x512MB
 Disk Subsystem: 2x73GB SCSI, 15K RPM
 Other Hardware: None

Software

OpenMP Threads: 16
 Parallel: OpenMP
 Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
 XL Fortran Enterprise Edition Version 10.1 for AIX
 Other Software: ESSL 4.2.0.3
 File System: AIX/JFS2
 System State: Multi-user

Notes/Tuning Information

Portability Flags & Environment Variables

-qfixed used in: 310.wupwise_m, 312.swim_m, 314.mgrid_m, 316.applu_m, 324.apsi_m
 -qfixed=80 used in: 318.galgel_m
 -qsuffix=f=f90 used in: 318.galgel_m, 326.gafort_m, 328.fma3d_m

Base Flags

C: -qpdf1/pdf2
 -q64 -O5 -qalign=natural -qhot=arraypad -Q -bdatapsize:64K -qsmp=omp
 FORTRAN: -O5 -qipa=noobject -qipa=partition=large -qmaxmem=-1 -qsmp=omp
 EXTRA_LDFLAGS=-bmaxdata:0x80000000

Base & Peak User Environment:

OMP_NUM_THREADS=16
 OMP_DYNAMIC=FALSE
 XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=1
 MALLOCMULTIHEAP=1

Peak Flags:

-qsmp=omp used in all cases
 310.wupwise_m: -O5 -qhot=arraypad -qipa=noobject -qipa=partition=large -qmaxmem=-1 -q64 -btextpsize:64K -bdatapsize:64K
 fdpr -q -O3
 312.swim_m: -O5 -qarch=pwr3 -qtune=pwr3 -q64 -btextpsize:64K -bdatapsize:64K -bstackpsize:64K
 314.mgrid_m: -O5 -qipa=partition=large -qalign=struct=natural -q64 -btextpsize:64K -bdatapsize:64K



OMPM2001 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 575 (2200 MHz, 8 CPU)

SPECompMpeak2001 = 40560

SPECompMbase2001 = 33521

SPEC license #HPG0005 Tested by: IBM Test site: Austin, TX Test date: Dec-2005 Hardware AvailFeb-2006 Software AvailFeb-2006

Notes/Tuning Information (Continued)

```

316.applu_m:      -O3 -qarch=pwr4 -qtune=pwr4 -q64 -btextpsize:64K -bdatapsize:64K
318.galgel_m:    -O5 -qarch=pwr3 -qtune=pwr3 -btextpsize:64K -bdatapsize:64K -bstacksize:64K -lmass -qessl -lesslsmp
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
320.earthquake_m: -qpdf1/pdf2
                  -O5 -qfdpr -q64 -bdatapsize:64K
                  fdpr -q -O3
325.apsi_m:      -O5 -qalign=struct=natural -bdatapsize:64K -bstacksize:64K
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
                  XLSMPOPTS=SPINS=0:YIELDS=0:STACK=8000000:SCHEDULE=STATIC:STARTPROC=0:STRIDE=2
326.gafort_m:    -O5 -qhot=arraypad -qipa=noobject -qipa=partition=large -qmaxmem=-1 -qalign=struct=natural
                  -btextpsize:64K -bdatapsize:64K -bstacksize:64K -lhmu -lmass -qessl -lesslsmp
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
328.fma3d_m:     -O5 -qhot=arraypad -qipa=noobject -qipa=partition=large -qmaxmem=-1 -btextpsize:64K -bdatapsize:64K
                  -bstacksize:64K -lmass -qessl -lesslsmp
                  EXTRA_LDFLAGS=-bmaxdata:0x80000000
330.art_m:       -qpdf1/pdf2
                  -O5 -qfdpr -q64 -btextpsize:64K -bdatapsize:64K -lesslsmp
                  fdpr -q -O3
                  EXTRA_CFLAGS= -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16
332.amp_m:       -qpdf1/pdf2
                  -O5 -qipa=partition=large -qmaxmem=-1 -q64 -btextpsize:64K -bdatapsize:64K

```

Alternate sources:

Add critical region around update of linked list in parallel loop.
Approved src.alt available as ompm-purdue1-20040324.tar.gz
Used for 330.art_m, base and peak.

Peak sources:

SPEC OMPL2001 source for 32bit systems modified for SPEC OMPM2001 used
with 312.swim_m, 316.applu_m, 320.earthquake_m, 326.gafort_m.

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Technology Level.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

SUT: Acronym for "System Under Test"

ESSL: Engineering and Scientific Subroutine Library

ANSI C89: IBM XL C for AIX invoked as xlc_r

Fortran 90: IBM XL Fortran for AIX invoked as xlf_r

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=1024 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:
submit = bindprocessor \\$\\$ \\$SPECUSERNUM; \$command

The "bindprocessor" AIX command binds a process to a CPU core.