

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

IBM: eServer xSeries 365
Zeus: Zeus V4.2r2

SPECweb99_SSL =2259

Test Date: Nov-2003
Tester: IBM

Hardware Avail: Dec-2003 OS Avail: Jun-2003 HTTPS Software Avail: Mar-2003 Sup. Software Avail: Mar-2003 SPEC license #: 11

Hardware

Vendor: IBM
Model: eServer xSeries 365
Processor: 2.8GHz Intel Xeon MP
Processors: 4 cores, 4 chips, 1 core/chip
Primary Cache: 12KBI+8KBD on chip
Secondary Cache: 512KB
Other Cache: 2GB L3 cache
Memory: 16 GB
Disk Subsystem: 6 36GB 15KRPM Ultra 320 SCSI Drives
Disk Controllers: On-board LSI controller
Other Hardware: 1 Nortel Networks Switch

Software

Operating System: Red Hat Linux 7.3
File System: ext2
Other Software: GCC 2.96

HTTPS Software

Vendor: Zeus
HTTPS Software: Zeus V4.2r2
API: Zeus PEPP 0.8 ISAPI used for Dynamic content
Server Cache: None
Log Mode: Zeus Binary CLF

Test Sponsor

Test Date: Nov-2003
Tested By: IBM
SPEC License: 11

Network

of Controllers: 1
Network Controllers: Intel PRO 1000 MT Dual Port Server Adapter
of Nets: 2
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 10
Model: IBM eServer xSeries 330
Processor: 933Mhz Pentium III
of Processors: 1
Memory: 512MB
Network Controller: IBM Netfinity Gigabit Ethernet Adapter
Operating System: Red Hat Linux 7.3
Compiler: GCC 2.96

Notes/Tuning Information

SUT Notes

3 U320 15K 36GB SCSI disk with EXT2 for OS/fileset
3 U320 15K 36GB SCSI disk with EXT2 for logs
Software RAID0 strip is used for for fileset and logs
Memory configuration 8 x 2GB PC2100 DIMMs

Operating System Notes

Tuning parameters:

- net.ipv4.ip_forward=1, default 0
 - net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
 - net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
 - net.ipv4.tcp_max_tw_buckets = 450000, sets TCP time-wait buckets pool size, default 180000
 - net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
 - net.core.wmem_default = 10000000, default send socket buffer size, default 65535
 - net.core.optmem_max = 10000000, default 10240
 - net.core.hot_list_length = 10000, maximum number of skb-heads to be cached, default 128
 - net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
 - net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
 - net.ipv4.tcp_mem = 30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
 - fs.file-max = 524288, maximum number of open files, default 1024
 - net.core.netdev_max_backlog=300000, number of unprocessed input packets before kernel starts dropping them, default 300"
- Kernel is Red Hat Linux (2.4.20-20.7xcustom). See IBM-20031211-config.txt
One NIC IRQ bound to logical processor 0 on physical processor 0, and second NIC irq bound to logical processor 0 on physical processor 1
Each NIC's TX queue length set to 20000 via ifconfig, default 100
Log & fileset partition mounted with "noatime,nodiratime", no inode access time updating

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes

Zeus Configuration

- tuning!so_wbuff_size 1048576
- tuning!softservers no
- tuning!cbuff_size 65536
- tuning!clientfirst_optimise yes
- tuning!ssl_sessioncache_size 7573
- tuning!sendfile yes
- tuning!sendfile_minsize 0
- tuning!sendfile_maxsize 0
- tuning!listen_queue_size 8192
- tuning!keepalive_timeout 20
- tuning!keepalive_max 1000
- tuning!maxaccept 64
- tuning!modules!cgi!enabled yes
- tuning!isapi!enabled yes
- modules!security!enabled yes

Virtual Server Configuration

- ip_name = server
- bindaddr = 192.0.1.100,192.0.2.100

See IBM-Zeus-tuning-20021224.txt for a description of the Zeus tuning parameters

ISAPI Source code is available in the SPECweb99_SSL support docs as HP-20020724-API.tar.gz

HTTP API Notes

Zeus ISAPI interface used

Zeus PEPP 0.8 ISAPI used for Dynamic content

./Configure --ssl=yes

Network Notes

Networking Tunable Parameters:

e1000 parameter: TxIntDelay = 32, change transmit interrupt delay, default 64

Client Notes

Client code generated with ./configure --enable-posix-threads

net.ipv4.ip_local_port_range 1024 65535