



# SPEC ACCEL™ OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

## Intel Intel Xeon Gold 6148


Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

SPECaccel\_omp\_peak = 5.61

SPECaccel\_omp\_base = 5.16

ACCEL license: 13  
Test sponsor: Intel  
Tested by: Intel

Test date: Jul-2017  
Hardware Availability: Jul-2017  
Software Availability: Oct-2017



### Hardware

CPU Name: Intel Xeon Gold 6148  
 CPU Characteristics: Simultaneous multithreading (SMT) ON, Turbo ON  
 CPU MHz: 2400  
 CPU MHz Maximum: 3700  
 FPU: Integrated  
 CPU(s) enabled: 40 cores, 2 chips, 20 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: 27.5 MB I+D on chip per chip  
 Other Cache: None

Continued on next page

### Accelerator

Accel Model Name: Intel Xeon Gold 6148  
 Accel Vendor: Intel  
 Accel Name: Intel Xeon Gold 6148  
 Type of Accel: CPU  
 Accel Connection: N/A  
 Does Accel Use ECC: yes  
 Accel Description: 2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON  
 Accel Driver: N/A



# SPEC ACCEL OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

## Intel Intel Xeon Gold 6148

Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

SPECaccel\_omp\_peak = 5.61

SPECaccel\_omp\_base = 5.16

ACCEL license: 13  
Test sponsor: Intel  
Tested by: Intel

Test date: Jul-2017  
Hardware Availability: Jul-2017  
Software Availability: Oct-2017

### Hardware (Continued)

Memory: 196 GB (12 x 16 GB 2Rx4 DDR4-2666 ECC Registered)  
Disk Subsystem: 108 TB Panasas ActiveStor 14  
Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 7.3 (Maipo)  
3.10.0-514.6.2.0.1.el7.x86\_64.knl1  
Compiler: C/C++/Fortran: Version 18.0 of Intel Composer XE for Linux Build  
File System: panfs  
System State: Run level 3 (default)  
Other Software: FFTW 3.3.6

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.postencil	43.7	2.49	45.7	2.39	<b><u>44.7</u></b>	<b><u>2.44</u></b>	43.7	2.49	45.7	2.39	<b><u>44.7</u></b>	<b><u>2.44</u></b>
504.polbm	39.1	3.12	41.1	2.97	<b><u>40.3</u></b>	<b><u>3.03</u></b>	39.1	3.12	41.1	2.97	<b><u>40.3</u></b>	<b><u>3.03</u></b>
514.pomriq	180	3.46	188	3.30	<b><u>182</u></b>	<b><u>3.42</u></b>	180	3.46	188	3.30	<b><u>182</u></b>	<b><u>3.42</u></b>
550.pmd	<b><u>51.0</u></b>	<b><u>4.73</u></b>	51.0	4.73	51.7	4.66	46.9	5.14	<b><u>46.7</u></b>	<b><u>5.16</u></b>	46.6	5.17
551.ppalm	<b><u>210</u></b>	<b><u>2.59</u></b>	209	2.60	210	2.59	<b><u>102</u></b>	<b><u>5.33</u></b>	99.2	5.48	103	5.27
552.pep	72.2	3.20	69.7	3.32	<b><u>70.0</u></b>	<b><u>3.30</u></b>	<b><u>65.1</u></b>	<b><u>3.55</u></b>	65.2	3.54	65.0	3.55
553.pclvrleaf	166	6.89	167	6.85	<b><u>166</u></b>	<b><u>6.89</u></b>	143	8.00	142	8.06	<b><u>143</u></b>	<b><u>8.01</u></b>
554.pcg	52.9	6.29	54.1	6.16	<b><u>53.0</u></b>	<b><u>6.28</u></b>	52.9	6.29	54.1	6.16	<b><u>53.0</u></b>	<b><u>6.28</u></b>
555.pseismic	92.5	3.05	90.9	3.10	<b><u>91.1</u></b>	<b><u>3.10</u></b>	<b><u>87.5</u></b>	<b><u>3.22</u></b>	87.7	3.21	85.7	3.29
556.psp	52.7	15.5	56.0	14.6	<b><u>52.7</u></b>	<b><u>15.5</u></b>	52.7	15.5	56.0	14.6	<b><u>52.7</u></b>	<b><u>15.5</u></b>
557.pcsp	<b><u>53.9</u></b>	<b><u>15.9</u></b>	55.3	15.5	53.6	16.0	<b><u>53.9</u></b>	<b><u>15.9</u></b>	55.3	15.5	53.6	16.0
559.pmniGhost	<b><u>93.4</u></b>	<b><u>4.25</u></b>	94.3	4.21	93.1	4.27	83.1	4.78	<b><u>83.1</u></b>	<b><u>4.78</u></b>	83.2	4.77
560.pilbdc	<b><u>155</u></b>	<b><u>4.22</u></b>	154	4.24	155	4.21	<b><u>152</u></b>	<b><u>4.30</u></b>	153	4.28	152	4.31
563.pswim	<b><u>47.3</u></b>	<b><u>3.36</u></b>	49.0	3.25	47.0	3.38	45.2	3.52	45.3	3.51	<b><u>45.2</u></b>	<b><u>3.52</u></b>
570.pbt	32.0	24.4	<b><u>32.2</u></b>	<b><u>24.2</u></b>	32.9	23.7	32.0	24.4	<b><u>32.2</u></b>	<b><u>24.2</u></b>	32.9	23.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

Sysinfo program  
/panfs/projects/innl/abobyrr/SpecACCEL\_OMP/kits/kit1.2\_skx\_18.0/Docs/sysinfo  
\$Rev: 6965 \$ \$Date:: 2015-04-21 ## c05a7f14b1b1765e3felfdf68447e8a35  
running on epb227 Tue Jul 18 06:09:41 2017

Continued on next page



# SPEC ACCEL OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

## Intel Intel Xeon Gold 6148

Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

SPECaccel\_omp\_peak = 5.61

SPECaccel\_omp\_base = 5.16

**ACCEL license:** 13  
**Test sponsor:** Intel  
**Tested by:** Intel

**Test date:** Jul-2017  
**Hardware Availability:** Jul-2017  
**Software Availability:** Oct-2017

### Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/accel/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) Gold 6148 CPU @ 2.40GHz
 2 "physical id"s (chips)
 80 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 20
siblings : 40
physical 0: cores 0 1 2 3 4 8 9 10 11 12 16 17 18 19 20 24 25 26 27 28
physical 1: cores 0 1 2 3 4 8 9 10 11 12 16 17 18 19 20 24 25 26 27 28
cache size : 28160 KB
```

```
From /proc/meminfo
MemTotal: 196699188 kB
HugePages_Total: 0
Hugepagesize: 2048 kB
```

```
From /etc/*release* /etc/*version*
oracle-release: Oracle Linux Server release 7.3
os-release:
NAME="Oracle Linux Server"
VERSION="7.3"
ID="ol"
VERSION_ID="7.3"
PRETTY_NAME="Oracle Linux Server 7.3"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:oracle:linux:7:3:server"
HOME_URL="https://linux.oracle.com/"
redhat-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
system-release: Oracle Linux Server release 7.3
system-release-cpe: cpe:/o:oracle:linux:7:3:server
```

```
uname -a:
Linux epb227 3.10.0-514.6.2.0.1.el7.x86_64.knl1 #1 SMP Thu Mar 2 10:19:17 MST
2017 x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Jul 17 12:09

```
SPEC is set to: /panfs/projects/innl/abobyr/SpecACCEL_OMP/kits/kit1.2_skx_18.0
Filesystem Type Size Used Avail Use% Mounted on
panfs://36.101.212.1/innl panfs 108T 41T 68T 38% /global/panfs02/innl
Additional information from dmidecode:
```

Continued on next page



# SPEC ACCEL OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

## Intel Intel Xeon Gold 6148

Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

SPECaccel\_omp\_peak = 5.61

SPECaccel\_omp\_base = 5.16

ACCEL license: 13

Test sponsor: Intel

Tested by: Intel

Test date: Jul-2017

Hardware Availability: Jul-2017

Software Availability: Oct-2017

## Platform Notes (Continued)

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfo program)

## General Notes

Used Environment Variables:

ENV\_KMP\_AFFINITY=compact,0 - assign OpenMP Threads continuously  
ENV\_OMP\_NUM\_THREADS=80 - limits number of Threads to be started  
ENV\_KMP\_HW\_SUBSET=2S,20C,2T - control Thread distribution across sockets, cores and hw threads  
ENV\_FORT\_BUFFERED=true - enables buffered I/O for Fortran  
ENV\_OMP\_DYNAMIC=FALSE - disable the dynamic adjustment of the number of threads within a team  
ENV\_KMP\_LIBRARY=turnaround - selects the OpenMP runtime library throughput  
ENV\_KMP\_BLOCKTIME=infinite - sets the time, in milliseconds, that a thread should wait, after completing the execution of a parallel region, before sleeping.

## Base Compiler Invocation

C benchmarks:

icc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

503.postencil: -DSPEC\_USE\_INNER\_SIMD  
504.polbm: -DSPEC\_USE\_INNER\_SIMD  
514.pomriq: -DSPEC\_USE\_INNER\_SIMD  
550.pmd: -DSPEC\_USE\_INNER\_SIMD -80  
551.ppalm: -DSPEC\_USE\_INNER\_SIMD  
552.pep: -DSPEC\_USE\_INNER\_SIMD  
553.pclvrleaf: -DSPEC\_USE\_INNER\_SIMD  
554.pcg: -DSPEC\_USE\_INNER\_SIMD  
555.pseismic: -DSPEC\_USE\_INNER\_SIMD  
556.psp: -DSPEC\_USE\_INNER\_SIMD

Continued on next page



# SPEC ACCEL OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

**Intel**  
**Intel Xeon Gold 6148**

Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

**SPECaccel\_omp\_peak = 5.61**

**SPECaccel\_omp\_base = 5.16**

**ACCEL license:** 13  
**Test sponsor:** Intel  
**Tested by:** Intel

**Test date:** Jul-2017  
**Hardware Availability:** Jul-2017  
**Software Availability:** Oct-2017

## Base Portability Flags (Continued)

557.pcsp: -DSPEC\_USE\_INNER\_SIMD  
559.pmniGhost: -DSPEC\_USE\_INNER\_SIMD -nofor-main  
560.pilbdc: -DSPEC\_USE\_INNER\_SIMD  
563.pswim: -DSPEC\_USE\_INNER\_SIMD  
570.pbt: -DSPEC\_USE\_INNER\_SIMD

## Base Optimization Flags

C benchmarks:  
-O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
Fortran benchmarks:  
-O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
Benchmarks using both Fortran and C:  
-O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host

## Peak Compiler Invocation

C benchmarks:  
icc  
Fortran benchmarks:  
ifort  
Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

503.postencil: -DSPEC\_USE\_INNER\_SIMD  
504.polbm: -DSPEC\_USE\_INNER\_SIMD  
514.pomriq: -DSPEC\_USE\_INNER\_SIMD  
550.pmd: -DSPEC\_USE\_INNER\_SIMD -80  
551.ppalms: -DSPEC\_USE\_INNER\_SIMD -DSPEC\_HOST\_FFTW3  
552.pep: -DSPEC\_USE\_INNER\_SIMD  
553.pclvrleaf: -DSPEC\_USE\_INNER\_SIMD  
554.pcg: -DSPEC\_USE\_INNER\_SIMD  
555.pseismic: -DSPEC\_USE\_INNER\_SIMD  
556.psp: -DSPEC\_USE\_INNER\_SIMD  
557.pcsp: -DSPEC\_USE\_INNER\_SIMD

Continued on next page



# SPEC ACCEL OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

## Intel Intel Xeon Gold 6148

Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

SPECaccel\_omp\_peak = 5.61

SPECaccel\_omp\_base = 5.16

**ACCEL license:** 13  
**Test sponsor:** Intel  
**Tested by:** Intel

**Test date:** Jul-2017  
**Hardware Availability:** Jul-2017  
**Software Availability:** Oct-2017

## Peak Portability Flags (Continued)

559.pmniGhost: -DSPEC\_USE\_INNER\_SIMD -nofor-main  
560.pilbdc: -DSPEC\_USE\_INNER\_SIMD  
563.pswim: -DSPEC\_USE\_INNER\_SIMD  
570.pbt: -DSPEC\_USE\_INNER\_SIMD

## Peak Optimization Flags

C benchmarks:

503.postencil: basepeak = yes  
504.polbm: basepeak = yes  
514.pomriq: basepeak = yes  
552.pep: -O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
-qopt-streaming-stores always -fimf-precision=low  
554.pcg: basepeak = yes  
557.pcsp: basepeak = yes  
570.pbt: basepeak = yes

Fortran benchmarks:

550.pmd: -O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
-fimf-precision=low  
551.ppalm: -O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
-I/home/abobyrr/FFTW-3.3.6\_SKL/include  
-L/home/abobyrr/FFTW-3.3.6\_SKL/lib  
555.pseismic: -O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
556.psp: basepeak = yes  
560.pilbdc: -O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
-qopt-prefetch=5  
563.pswim: Same as 555.pseismic

Benchmarks using both Fortran and C:

-O3 -xCOMMON-AVX512 -qopenmp -qopenmp-offload=host  
-qopt-streaming-stores always



# SPEC ACCEL OMP Result

Copyright 2015-2017 Standard Performance Evaluation Corporation

**Intel**  
**Intel Xeon Gold 6148**

Intel Server System R2208WFTZS (2 x Intel Xeon Gold 6148, 2.40 GHz, SMT ON, Turbo ON) Endeavour Node

**SPECaccel\_omp\_peak = 5.61**

**SPECaccel\_omp\_base = 5.16**

**ACCEL license:** 13  
**Test sponsor:** Intel  
**Tested by:** Intel

**Test date:** Jul-2017  
**Hardware Availability:** Jul-2017  
**Software Availability:** Oct-2017

## Peak Other Flags

Fortran benchmarks:

551.ppalm: -lfftw3

The flags file that was used to format this result can be browsed at  
<https://www.spec.org/accel/flags/Intel-icc18.0-linux64.20170802.html>

You can also download the XML flags source by saving the following link:  
<https://www.spec.org/accel/flags/Intel-icc18.0-linux64.20170802.xml>

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC ACCEL v1.2.  
Report generated on Wed Aug 2 12:35:20 2017 by SPEC ACCEL PS/PDF formatter v1290.  
Originally published on 2 August 2017.