



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2200 2X 400MHz R12k

SPECfp_rate2000 = 6.70
SPECfp_rate_base2000 = 6.25

SPEC license #: 4 Tested by: SGI Test date: Apr-2000 Hardware Avail: Jun-2000 Software Avail: Apr-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	634	5.85	2	555	6.69
171.swim	2	1783	4.03	2	1840	3.91
172.mgrid	2	1134	3.68	2	1094	3.82
173.applu	2	1077	4.53	2	999	4.87
177.mesa	2	486	6.68	2	458	7.08
178.galgel	2	293	22.9	2	255	26.4
179.art	2	246	24.5	2	246	24.6
183.equake	2	775	3.89	2	769	3.92
187.facerec	2	511	8.63	2	506	8.71
188.amp	2	569	8.97	2	571	8.93
189.lucas	2	1205	3.85	2	1211	3.83
191.fma3d	2	1398	3.49	2	1174	4.15
200.sixtrack	2	555	4.60	2	549	4.65
301.apsi	2	1194	5.05	2	824	7.32

Hardware

CPU: R12000
 CPU MHz: 400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2, 4, 6, 8
 Parallel: No
 Primary Cache: 32KBI + 32KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2048MB
 Disk Subsystem: 2 x 18 GB SCSI (striped)
 Other Hardware: None

Software

Operating System: IRIX 6.5.8f
 Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90
 SCSL 1.2 Math Library
 File System: xfs
 System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):
 PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
 PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
 Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2
 Portability Flags:
 178.galgel: -fixedform
 Peak optimization flags:
 note: all occurrences of (FEEDBACK) below means compiled with a two-step process:
 PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000 -INLINE:aggressive=on
 .
 -OPT:Olimit=0 -LNO:fusion=2:prefetch Ahead=5
 171.swim: -Ofast=ip27 -LNO:cs2=8m:fission=2:ou=2
 172.mgrid: -Ofast=ip27 -LNO:cs2=8m:fission=2:ou=2
 173.applu: -Ofast=ip27 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2
 177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0 (FEEDBACK)
 178.galgel: -Ofast=ip27 -LNO:ou_max=7 -lscs (FEEDBACK)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2200 2X 400MHz R12k

SPECfp_rate2000 = 6.70
SPECfp_rate_base2000 = 6.25

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

Notes/Tuning Information (Continued)

```
.
  RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -IPA:min_hot=15 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -fb_opt /tmp/SPEC2000/FBDIR_peak/$(EXEBASE) -LNO:fusion=2 (FEEDBACK)
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -OPT:goto=off:unroll_size=160:unroll_times_max=4
  -CG:ld_latency=2 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
The following O/S parameters were set:
  setenv PAGESIZE_DATA 4096
  setenv PAGESIZE_TEXT 4096
  setenv PAGESIZE_STACK 4096
  systune -i ; percent_totalmem_4m_pages = 50 ; nlpages_4m = 128
  limit stacksize 500000
The following is done before building each benchmark that requires (FEEDBACK):
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
or
rm -rf /tmp/SPEC2000/FBDIR_base/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_base/$baseexe
```