



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel VC820 (866 MHz, Pentium III processor)

SPECint2000 = 407
SPECint_base2000 = 400

SPEC license #: 13 Tested by: Intel Corporation Test date: Nov-2000 Hardware Avail: Mar-2000 Software Avail: Nov-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	300	466	292	480
175.vpr	1400	445	315	444	315
176.gcc	1100	313	351	313	351
181.mcf	1800	666	270	666	270
186.crafty	1000	220	455	220	455
197.parser	1800	571	315	570	316
252.eon	1300	242	538	217	600
253.perlbmk	1800	339	531	339	531
254.gap	1100	280	392	280	393
255.vortex	1900	299	635	294	646
256.bzip2	1500	434	346	420	357
300.twolf	3000	868	346	865	347

Hardware

CPU: Pentium III processor (866 MHz, 133 MHz bus)
CPU MHz: 866
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 16KBI + 16KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
Disk Subsystem: IBM DTLA-307030 ATA-100
Other Hardware: Creative Labs Annihalator 2

Software

Operating System: Windows 2000 (Build 2195)
Compiler: Intel C/C++ Compiler 5.0,
Microsoft Visual C++ 6.0 (for libraries),
Other software: Microquill SmartHeap V5.0
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxK -Qipo shlw32M.lib +FDO
Base tuning for C++ programs: -QxK -Qipo -GX -GR
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip, 175.vpr, 176.gcc, 181.mcf, 186.crafty, 197.parser, 253.perlbmk, 254.gap:
-QxK -Qipo FDO shlw32M.lib
255.vortex, 256.bzip2, 300.twolf:
-QxK -Qipo FDO -Oa shlw32M.lib
252.eon:
-QxK -Qipo +FDO
Tested systems can be used with Shin-G ATX case, Sparkle Inc.,
power supply. Product description located as of 03/2000:
http://developer.intel.com/design/motherbd/vc/vc_ds.htm
Motherboard is available through Intel OEM Distribution Channel. See
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel VC820 (866 MHz, Pentium III processor)

SPECint2000 =	407
SPECint_base2000 =	400

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Nov-2000 | Hardware Avail: Mar-2000 | Software Avail: Nov-2000

Notes/Tuning Information (Continued)

<http://channel.intel.com/> for more information
The system bus runs at 133 MHz