



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel VC820 (933 MHz, Pentium III processor)

SPECint2000 = 429
SPECint_base2000 = 423

SPEC license #: 13 Tested by: Intel Corporation Test date: Nov-2000 Hardware Avail: Mar-2000 Software Avail: Nov-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	278	503	277	505
175.vpr	1400	427	328	426	328
176.gcc	1100	300	367	300	367
181.mcf	1800	657	274	656	274
186.crafty	1000	204	490	204	490
197.parser	1800	543	332	542	332
252.eon	1300	224	581	201	648
253.perlbnk	1800	316	569	316	570
254.gap	1100	267	412	267	412
255.vortex	1900	281	675	277	687
256.bzip2	1500	413	363	401	374
300.twolf	3000	834	360	830	361

Hardware

CPU: Pentium III processor (933 MHz, 133 MHz bus)
 CPU MHz: 933
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 16KBI + 16KBD on chip
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
 Disk Subsystem: IBM DTLA-307030 ATA-100
 Other Hardware: Creative Labs Annihalator 2

Software

Operating System: Windows 2000 (Build 2195)
 Compiler: Intel C/C++ Compiler 5.0,
 Microsoft Visual C++ 6.0 (for libraries),
 Other software: Microquill SmartHeap V5.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxK -Qipo shlw32M.lib +FDO
Base tuning for C++ programs: -QxK -Qipo -GX -GR
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip, 175.vpr, 176.gcc, 181.mcf, 186.crafty, 197.parser, 253.perlbnk, 254.gap:
-QxK -Qipo FDO shlw32M.lib
255.vortex, 256.bzip2, 300.twolf:
-QxK -Qipo FDO -Oa shlw32M.lib
252.eon:
-QxK -Qipo +FDO
Tested systems can be used with Shin-G ATX case, Sparkle Inc.,
power supply. Product description located as of 03/2000:
http://developer.intel.com/design/motherbd/vc/vc_ds.htm
Motherboard is available through Intel OEM Distribution Channel. See
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation
Intel VC820 (933 MHz, Pentium III processor)

SPECint2000 =	429
SPECint_base2000 =	423

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Nov-2000 | Hardware Avail: Mar-2000 | Software Avail: Nov-2000

Notes/Tuning Information (Continued)

<http://channel.intel.com/> for more information
The system bus runs at 133 MHz