



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 3400 16X 500MHz R14k

SPECint_rate2000 = 77.5
SPECint_rate_base2000 = 75.0

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2001 | Hardware Avail: Jul-2001 | Software Avail: Mar-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	518	50.2	16	499	52.1
175.vpr	16	298	87.1	16	286	90.7
176.gcc	16	296	68.9	16	295	69.3
181.mcf	16	273	122	16	279	120
186.crafty	16	246	75.5	16	244	76.1
197.parser	16	526	63.5	16	500	66.8
252.eon	16	300	80.5	16	287	84.0
253.perlbnk	16	588	56.9	16	588	56.9
254.gap	16	428	47.6	16	427	47.8
255.vortex	16	329	107	16	291	121
256.bzip2	16	372	74.8	16	330	84.3
300.twolf	16	546	102	16	554	101

Hardware		Software	
CPU:	R14000	Operating System:	IRIX 6.5.11f
CPU MHz:	500	Compiler:	MIPSpro 7.3.1.2m C, C++, Fortran90
FPU:	Integrated	File System:	SCSL 1.3 Math Library
CPU(s) enabled:	16 cores, 16 chips, 1 core/chip	System State:	Single-user
CPU(s) orderable:	4-32		
Parallel:	No		
Primary Cache:	32KBI + 32KBD on chip		
Secondary Cache:	8MB(I+D) off chip		
L3 Cache:	N/A		
Other Cache:	N/A		
Memory:	16 GB		
Disk Subsystem:	1 x 18 GB FC, 24 x 18 GB FC (striped)		
Other Hardware:	None		

Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):
 PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)
 PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:
 176.gcc: -DUSG -Dalloca=__builtin_alloca -DMIPS -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSGI
 252.eon: -lm
 253.perlbnk: -DSPEC_CPU2000_SGI -DI_FCNTL
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_IOCTL_PROTO
 -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
 300.twolf: -DHAVE_SIGNED_CHAR

Peak optimization flags:
 note: all occurrences of (FEEDBACK) below means compiled with a two-step process:
 PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)
 175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee_limit=5000:linear=on
 . -LNO:prefetch Ahead=2 -INLINE:aggressive=on
 . -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld_latency=10 -lmalloc (FEEDBACK)
 181.mcf: -Ofast=ip27 -lmalloc (FEEDBACK)



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Origin 3400 16X 500MHz R14k

SPECint_rate2000 = 77.5

SPECint_rate_base2000 = 75.0

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2001 | Hardware Avail: Jul-2001 | Software Avail: Mar-2001

Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip27 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
. (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
. -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic
. -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
. -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: -Ofast=ip27 -IPA:use_intrinsic (FEEDBACK)

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
systemd -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
systemd -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
systemd -i ; r12k_bdiag = 0x4000000 ;
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak

```