



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER600 (600MHz)

SPECint_rate2000 = 37.2
SPECint_rate_base2000 = 34.4

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Sep-2001 Hardware Avail: Aug-2001 Software Avail: Dec-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	407	31.9	8	401	32.4
175.vpr	8	406	32.0	8	390	33.3
176.gcc	8	431	23.7	8	294	34.8
181.mcf	8	455	36.7	8	437	38.2
186.crafty	8	269	34.4	8	216	43.0
197.parser	8	460	36.3	8	445	37.6
252.eon	8	308	39.2	8	288	41.9
253.perlbnk	8	426	39.2	8	413	40.5
254.gap	8	528	19.3	8	515	19.8
255.vortex	8	331	53.2	8	325	54.2
256.bzip2	8	377	37.0	8	377	36.9
300.twolf	8	661	42.1	8	619	45.0

Hardware

CPU: SPARC64 GP
 CPU MHz: 600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
 CPU(s) orderable: 2 to 8
 Parallel: None
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 8MB(I+D) off chip, per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 32GB
 Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
 Other Hardware: None

Software

Operating System: Solaris 8 7/01
 Compiler: Fujitsu Parallelnavi 1.0.2
 with patch 911403-01
 Sun Forte Developer 6 update 2
 File System: ufs
 System State: single user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage
 fdo_pre0=rm -rf `pwd`/*.fbk
 PASS1=-Kpg
 PASS2=-Kpu=\$(EXEBASE).fbk
 (252.eon, for Forte Developer 6 update 2): -fast -xcrossfile -xarch=v8plus
 fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
 PASS1=-xprofile=collect:`pwd`/../feedback
 PASS2=-xprofile=use:`pwd`/../feedback

Peak (for Parallelnavi 1.0.2):
 fdo_pre0=rm -rf `pwd`/*.fbk
 PASS1=-Kpg
 PASS2=-Kpu=\$(EXEBASE).fbk
 164.gzip: -Kfast_GP=4,largepage
 175.vpr: -Kfast_GP=4,staticclump,memalias,switchopt,cond,GREG,nounroll,largepage,onefile,NOFLTLTD=3,xi=30
 181.mcf: -Kfast_GP=2,nounroll,memalias,restp,prefetch=2,largepage -x-
 197.parser: -Kfast_GP=4,switchopt,cond,staticclump,use_rodata,largepage
 253.perlbnk: -Kfast_GP=4,memalias,switchopt,largepage,bcopy
 254.gap: -Kfast_GP=3,largepage,memalias,unroll=4
 256.bzip2: -Kfast_GP=3,largepage



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER600 (600MHz)

SPECint_rate2000 = 37.2
SPECint_rate_base2000 = 34.4

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Sep-2001 | Hardware Avail: Aug-2001 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```

300.twolf: -Kfast_GP=5,GREG,memalias,cfunc,staticclump,use_rodata,xi=10,largepage,nounroll,bcopy
(for Forte Developer 6 update 2)
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qiselect-funcalign=64
-xarch=v8plus -xprefetch -DUSG
186.crafty: -fast -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong
-xregs=syst -xchip=ultra2 -xarch=v8plus -W2,-Amemopt
252.eon: -fast -xcrossfile -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
-Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
-Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
-xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus -W2,-Amemopt

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon: -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

```

Note:

```

System Tunables: (for /etc/system)
consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
shmsys:shminfo_shmmax=8589934592, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024
(for /etc/opt/FJSPvnm/lpg.conf)
TSS=512M, SHMSEGSIZE=256M
ONESTEP=yes was set for all baseline and peak benchmarks.
Feedback directed optimization was used for all baseline and peak benchmarks.

```