



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation  
RS/6000 44P-270 (450MHz, 8MBL2)

SPECfp2000 = 433

SPECfp\_base2000 = 426

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Sep-2001 | Hardware Avail: Oct-2001 | Software Avail: Dec-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	277	577	277	577	
171.swim	3100	772	402	772	402	
172.mgrid	1800	546	330	546	330	
173.applu	2100	651	323	648	324	
177.mesa	1400	432	324	420	333	
178.galgel	2900	303	958	303	958	
179.art	2600	242	1074	240	1084	
183.earthquake	1300	248	524	228	571	
187.facerec	1900	417	455	417	455	
188.amp	2200	603	365	588	374	
189.lucas	2000	704	284	681	294	
191.fma3d	2100	598	351	584	359	
200.sixtrack	1100	432	255	432	255	
301.apsi	2600	718	362	718	362	

### Hardware

CPU: POWER3-II  
CPU MHz: 450  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 2,4  
Parallel: No  
Primary Cache: 32KBI+64KBD (on chip)  
Secondary Cache: 8MB unified (off chip)  
L3 Cache: None  
Other Cache: None  
Memory: 2GB  
Disk Subsystem: 2x18GB 10000RPM  
Other Hardware: None

### Software

Operating System: AIX 5L V5.1  
Compiler: Fortran 77 and 90: IBM xl Fortran 7.1.1.0 invoked as 'xlf90' for Fortran 90 and as xlf for Fortran 77  
C: IBM VAC++ 5.0.2.0 invoked as 'xlc'  
File System: AIX/JFS  
System State: Multi-user

## Notes/Tuning Information

### Portability Flags

-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi  
-qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

### Base Optimization Flags:

Fortran: -O5 -lmass  
C: -O5 -lmass

### Peak Optimization Flags

168.wupwise: (basepeak=1)  
171.swim: (basepeak=1)  
172.mgrid: (basepeak=1)  
173.applu: -O5 -lmass -qipa=partition=large  
177.mesa: -O5 -lmass -qipa=partition=large, fdpr -v -R3  
178.galgel: (basepeak=1)  
179.art: -O5 -lmass -qalign=natural  
183.earthquake: -O5 -lmass -lhmu -qinline  
187.facerec: (basepeak=1)  
188.amp: -O3 -qarch=pwr3



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation  
RS/6000 44P-270 (450MHz, 8MBL2)

SPECfp2000 =	433
SPECfp_base2000 =	426

SPEC license #:	11	Tested by:	IBM Corp.	Test date:	Sep-2001	Hardware Avail:	Oct-2001	Software Avail:	Dec-2001
-----------------	----	------------	-----------	------------	----------	-----------------	----------	-----------------	----------

## Notes/Tuning Information (Continued)

```
189.lucas:      -qpdf1/pdf2 -O3 -lhm -lmas
                -qipa=partition=large, fdpr -v -R3
191.fma3d:      -O4 -lmas -qipa=partition=large
200.sixtrack:   (basepeak=1)
301.apsi:       (basepeak=1)
fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O
APAR IY 21957 was applied to AIX 5L V5.1 to enable new hardware support
```