



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1600+

SPECint2000 = 595

SPECint_base2000 = 572

SPEC license #: 49 Tested by: AMD Austin TX Test date: Sep-2001 Hardware Avail: Oct-2001 Software Avail: Jul-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	204	687	200	701	
175.vpr	1400	391	358	363	386	
176.gcc	1100	284	387	238	463	
181.mcf	1800	683	263	681	264	
186.crafty	1000	122	821	122	822	
197.parser	1800	350	515	349	516	
252.eon	1300	116	1120	104	1246	
253.perlbnk	1800	211	852	211	851	
254.gap	1100	168	653	168	653	
255.vortex	1900	216	879	214	887	
256.bzip2	1500	315	476	299	501	
300.twolf	3000	673	446	661	454	

Hardware

CPU: AMD Athlon (TM) XP 1600+
 CPU MHz: 1400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x128MB PC2100 DDR SDRAM CL2 Micron
 Disk Subsystem: IBM DPTA-372020
 Other Hardware: None

Software

Operating System: Windows 2000 SP2
 Compiler: Intel C/C++ 5.0.1 build 010525Z
 Microsoft Visual Studio 6.0 SP5 (libraries)
 MicroQuill SmartHeap Library 5.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -QxK -Qipo +FDO shlw32M.lib

Baseline C++: -QxK -Qipo -GX -GR

Peak tuning:

164.gzip: -O3 -QxK -Qwp_ipo -Oi- +FDO

175.vpr: -O3 -Qxi -QaxK -Qwp_ipo +FDO

176.gcc: -O3 -QxK -Qwp_ipo -Oi- +FDO shlw32M.lib

181.mcf: -O3 -Qxi -QaxK -Qwp_ipo +FDO

186.crafty: -O3 -QxK -Qwp_ipo -Oa +FDO shlw32M.lib

197.parser: -O3 -Qxi -QaxK -Qwp_ipo +FDO

252.eon: -O3 -QxiM -Qwp_ipo +FDO

253.perlbnk: -O3 -QxK -Qipo +FDO shlw32M.lib

254.gap: -O3 -QxK -Qipo -Oi- +FDO shlw32M.lib

255.vortex: -O3 -QxK -Qwp_ipo +FDO shlw32M.lib

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org>



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1600+

SPECint2000 = 595

SPECint_base2000 = 572

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Sep-2001 | Hardware Avail: Oct-2001 | Software Avail: Jul-2001

Notes/Tuning Information (Continued)

```
256.bzip2:    -O3 -QxK -Oa -Qwp_ipo
300.twolf:    -O3 -QxK -Qipo -Oa +FDO shlw32M.lib
ONESTEP is used for all base and peak runs
```

The tested system can be assembled using an ATX case such as the Antec KS-282, a 300W power supply such as the Sparkle FSP300-60GT, and a PCI or AGP video card. The System bus runs at 266MHz