



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1500 (1.062GHz)

SPECfp2000 = 884
SPECfp_base2000 = 757

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jun-2003 Hardware Avail: Sep-2003 Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	197	812	183	876
171.swim	3100	365	850	180	1724
172.mgrid	1800	311	579	311	579
173.applu	2100	327	643	266	789
177.mesa	1400	238	589	222	631
178.galgel	2900	234	1239	208	1392
179.art	2600	38.5	6751	35.7	7291
183.earth	1300	104	1255	96.8	1343
187.facerec	1900	206	922	188	1011
188.amp	2200	560	393	562	391
189.lucas	2000	602	332	322	620
191.fma3d	2100	439	479	397	529
200.sixtrack	1100	301	365	286	384
301.apsi	2600	430	605	430	605

Hardware

CPU: UltraSPARC IIIi
CPU MHz: 1062
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 1MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 4GB (4x1GB DIMM)
Disk Subsystem: 1 x 80GB IDE
Other Hardware: None

Software

Operating System: Solaris 8 HW 5/03
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:384 -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp:b6,-Ainline:cs=700
(no feedback)
172.mgrid: -fast -xipo=2



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1500 (1.062GHz)

SPECfp2000 = 884
SPECfp_base2000 = 757

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Jun-2003 | Hardware Avail: Sep-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

173.applu:  -fast -xipo=2
            -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
            -Qoption iropt -Aujam:inner=g
177.mesa:   -fast -xipo=2 -xalias_level=strong -xrestrict
            -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art:    -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ampp:   -fast -xipo=2 -xalias_level=std -lmopt -lm
189.lucas:  -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
            -Qoption f90comp -array_pad_rows,1977
191.fma3d:  -fast -stackvar -xprefetch_level=3
            -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi:   -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```