



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Bull
NovaScale 5160 HPC 8 way (1500MHz)

SPECfp_rate2000 = 152
SPECfp_rate_base2000 = 151

SPEC license #: 20 | Tested by: JFL | Test date: Jul-2003 | Hardware Avail: Sep-2003 | Software Avail: Sep-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	137	109	8	137	109
171.swim	8	161	178	8	161	178
172.mgrid	8	152	110	8	151	111
173.applu	8	69.0	282	8	69.0	282
177.mesa	8	128	101	8	128	101
178.galgel	8	72.5	371	8	72.5	371
179.art	8	38.3	630	8	38.3	630
183.equake	8	83.5	144	8	83.5	144
187.facerec	8	120	147	8	120	147
188.amp	8	194	105	8	194	105
189.lucas	8	173	107	8	169	110
191.fma3d	8	228	85.4	8	228	85.4
200.sixtrack	8	77.5	132	8	77.5	132
301.apsi	8	290	83.1	8	263	91.8

Hardware

CPU: Itanium 2 processor 1500 MHz
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 4 to 16
Parallel: No
Primary Cache: 16KBI + 16KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: 6MB (I+D) off chip
Other Cache: N/A
Memory: 64 GB (4 * 16 * 1GB DIMMs)
Disk Subsystem: 1 SJ0812 Disk drawer with
2 15krpm 36GB SCSI disks
Other Hardware: Hardware configuration: 4 modules of 2 CPUs

Software

Operating System: Linux 64 bit : Red Hat Advanced Server 2.1 + Bull expansion Pack
Compiler: Intel(R) Fortran Compiler for Linux 7.1 (Build 20030605)
Intel(R) C++ Compiler for Linux 7.1 (Build 20030605)
File System: ext2
System State: multi User

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO -ansi_alias
Fortran programs: -ipo -O3 +FDO

Portability Flags:

178.galgel: -FI

Peak optimization flags:

168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: -O3 -ipo
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: basepeak=yes



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Bull

NovaScale 5160 HPC 8 way (1500MHz)

SPECfp_rate2000 = 152

SPECfp_rate_base2000 = 151

SPEC license #: 20 | Tested by: JFL | Test date: Jul-2003 | Hardware Avail: Sep-2003 | Software Avail: Sep-2003

Notes/Tuning Information (Continued)

179.art: basepeak=yes
183.quake: basepeak=yes
187.facerec: basepeak=yes
188.amp: basepeak=yes
189.lucas: -O3 -ipo
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: -O3 -ipo

16 CPU machine with only 8 CPU enabled
8 CPU disabled by the service processor before booting