



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Bull
NovaScale 5080 (1500MHz)

SPECint_rate2000 = 92.0

SPECint_rate_base2000 = 91.3

SPEC license #: 20 | Tested by: JFL | Test date: Jul-2003 | Hardware Avail: Sep-2003 | Software Avail: Sep-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	153	84.9	8	153	84.9
175.vpr	8	151	86.2	8	151	86.2
176.gcc	8	92.6	110	8	86.7	118
181.mcf	8	242	69.0	8	242	69.0
186.crafty	8	96.0	96.6	8	93.9	98.8
197.parser	8	249	67.0	8	249	67.1
252.eon	8	104	116	8	104	116
253.perlbnk	8	176	95.1	8	176	95.1
254.gap	8	167	61.2	8	167	61.2
255.vortex	8	134	132	8	133	133
256.bzip2	8	151	92.4	8	151	92.4
300.twolf	8	247	113	8	247	113

Hardware

CPU: Itanium 2 processor 1500 MHz
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 4 to 8
Parallel: No
Primary Cache: 16KBI + 16KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: 6MB (I+D) off chip
Other Cache: N/A
Memory: 32 GB (2 * 16 * 1GB DIMMs)
Disk Subsystem: 1 SJ0812 Disk drawer with
2 15krpm 36GB SCSI disks
Other Hardware:

Software

Operating System: Linux 64 bit : Red Hat Advanced Server 2.1 + Bull expansion Pack
Compiler: Intel(R) C++ Compiler for Linux 7.1 (Build 20030605)
File System: ext2
System State: multi User

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO
C++ programs: -ipo -O2 +FDO -ansi_alias

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
186.crafty: -DLINUX_i386
252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
255.vortex: -DSPEC_CPU2000_LP64

Peak optimization flags:

164.gzip: basepeak=yes
175.vpr: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Bull
NovaScale 5080 (1500MHz)

SPECint_rate2000 = 92.0

SPECint_rate_base2000 = 91.3

SPEC license #: 20 | Tested by: JFL | Test date: Jul-2003 | Hardware Avail: Sep-2003 | Software Avail: Sep-2003

Notes/Tuning Information (Continued)

```
176.gcc: +FDO -ipo -O2
164.gzip: basepeak=yes
186.crafty: +FDO -ipo -O2
197.parser: +FDO -ipo -O2
252.eon: basepeak=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
255.vortex: +FDO -ipo -O2
256.bzip2: basepeak=yes
300.twolf: basepeak=yes
```