



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## IBM Corporation

eServer 325, 2.0 GHz Opteron, 64-bit pgi, SuSE SLES8 Linux

SPECfp\_rate2000 = 13.7

SPECfp\_rate\_base2000 = 13.6

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: Jul-2003 | Hardware Avail: Oct-2003 | Software Avail: Jul-2003

				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
24	21	18	15	168.wupwise	1	122	15.2	1	122	15.2
				171.swim	1	182	19.8	1	182	19.8
				172.mgrid	1	168	12.4	1	170	12.3
				173.applu	1	211	11.5	1	208	11.7
				177.mesa	1	96.2	16.9	1	91.4	17.8
				178.galgel	1	143	23.6	1	143	23.5
				179.art	1	220	13.7	1	218	13.9
				183.equake	1	106	14.2	1	104	14.5
				187.facerec	1	153	14.4	1	154	14.3
				188.amp	1	201	12.7	1	195	13.1
				189.lucas	1	187	12.4	1	187	12.4
				191.fma3d	1	175	13.9	1	176	13.8
				200.sixtrack	1	220	5.80	1	220	5.80
				301.apsi	1	251	12.0	1	251	12.0

### Hardware

CPU: AMD Opteron 246  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip  
 Secondary Cache: 1024KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 2 x 512MB PC2700 Reg ECC DDR SDRAM CL2.5  
 Disk Subsystem: 1 x 36GB 10Krpm SCSI  
 Other Hardware: None

### Software

Operating System: SuSE Linux 8.0 SLES 64 bit Kernel k\_deflt-2.4.19-249 (from SP2)  
 Compiler: PGI Fortran 5.0-1  
 SuSE gcc33 optional compiler (from SLES8 SP2)  
 File System: Linux/reiserfs  
 System State: Multi-user SuSE Run level 5

## Notes/Tuning Information

```
+FDO: PASS1=-fprofile-arcs PASS2=-fbranch-probabilities
fdo_pre0 = rm -f *.da *.life analyz_prbprob.out
pgf90 is the PGI Fortran compiler
gcc is the SuSE optional gcc33 package C compiler (from SLES8 SP2)
Portability:
  178.galgel:      -Mfixed
Baseline: C      -O3 -funroll-all-loops +FDO
Baseline: Fortran pgf90 -fastsse -Mipa=fast
Peak tuning:
  168.wupwise:    basepeak=true
  171.swim:       basepeak=true
  172.mgrid:      pgf90 -fast -Mipa=fast
  173.applu:      pgf90 -fast -Mipa=fast
  177.mesa:       gcc -O3 -finline-limit=2000 -funroll-all-loops +FDO
  178.galgel:     pgf90 -fastsse -Mipa=fast,align
  179.art:        gcc -O3 -funroll-all-loops -ffast-math -finline-limit=1500 +FDO
  183.equake:     gcc -O3 -funroll-all-loops -ffast-math -finline-limit=2000
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

eServer 325, 2.0 GHz Opteron, 64-bit pgi, SuSE SLES8 Linux

SPECfp\_rate2000 = 13.7

SPECfp\_rate\_base2000 = 13.6

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: Jul-2003 | Hardware Avail: Oct-2003 | Software Avail: Jul-2003

## Notes/Tuning Information (Continued)

```
187.facerec:    pgf90 -fastsse -Mipa=fast,align
188.amp:       gcc -O3 -funroll-all-loops -ffast-math -finline-limit=2000 +FDO
189.lucas:     basepeak=true
191.fma3d:     pgf90 -fastsse -Mipa=fast -Mnosmart
200.sixtrack:  basepeak=true
301.apsi:      pgf90 -fastsse -Mipa=fast -O3
ONESTEP is used for all base and peak runs
Only 1 CPU installed in system
Set the following BIOS parameters
BIOS: M1E108AUS 07/14/03
  DRAM Interleave = AUTO
  Node Interleave = AUTO
  ACPI SRAT       = Disabled
```