



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1500 (1.5GHz)

SPECfp2000 = 1272
SPECfp_base2000 = 1133

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Dec-2004 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	128	1251	116	1376
171.swim	3100	335	926	170	1824
172.mgrid	1800	243	741	246	733
173.applu	2100	226	931	186	1128
177.mesa	1400	167	838	145	968
178.galgel	2900	142	2047	121	2391
179.art	2600	24.2	10761	22.4	11615
183.earth	1300	80.1	1623	74.2	1751
187.facerec	1900	107	1782	106	1799
188.amp	2200	397	554	377	583
189.lucas	2000	231	866	231	866
191.fma3d	2100	331	634	304	690
200.sixtrack	1100	216	509	206	535
301.apsi	2600	300	868	293	887

Hardware

CPU: UltraSPARC IIIi
CPU MHz: 1503
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 1MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 4GB (4x1GB DIMM)
Disk Subsystem: 1 x 120GB IDE
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Sun Studio 9
Sun Performance Library 9
File System: ufs
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp,-Ainline:cs=700
(no feedback)
172.mgrid: -fast -xipo=2



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1500 (1.5GHz)

SPECfp2000 = 1272
SPECfp_base2000 = 1133

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Dec-2004 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

173.applu:  -fast -xipo=2
            -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
            -Qoption iropt -Aujam:inner=g
177.mesa:   -fast -xipo=2 -xalias_level=strong -xrestrict
            -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art:    -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.quake:  -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ampp:   -fast -xarch=v9b -xipo=2 -xalias_level=std -lmopt -lm
189.lucas:  basepeak=yes
191.fma3d:  -fast -xipo=2 -stackvar -xprefetch_level=3
            -Qoption iropt -Apf:pdl=1
200.sixtrack: -xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2 -xprefetch=no
301.apsi:   -fast -xcrossfile

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```