



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Blade 1500 (1.5GHz)

SPECfp\_rate2000 = 14.8

SPECfp\_rate\_base2000 = 13.1

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Dec-2004 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	128	14.5	1	116	16.0
171.swim	1	335	10.7	1	170	21.2
172.mgrid	1	243	8.60	1	246	8.50
173.applu	1	226	10.8	1	186	13.1
177.mesa	1	167	9.72	1	145	11.2
178.galgel	1	142	23.7	1	121	27.7
179.art	1	24.2	125	1	22.4	135
183.equake	1	80.1	18.8	1	74.2	20.3
187.facerec	1	107	20.7	1	106	20.9
188.amp	1	397	6.42	1	377	6.76
189.lucas	1	231	10.0	1	231	10.0
191.fma3d	1	331	7.36	1	304	8.01
200.sixtrack	1	216	5.90	1	206	6.21
301.apsi	1	300	10.1	1	293	10.3

### Hardware

CPU: UltraSPARC IIIi  
CPU MHz: 1503  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 32KBI+64KBD on chip  
Secondary Cache: 1MB(I+D) off chip  
L3 Cache: None  
Other Cache: None  
Memory: 4GB (4x1GB DIMM)  
Disk Subsystem: 1 x 120GB IDE  
Other Hardware: None

### Software

Operating System: Solaris 10  
Compiler: Sun Studio 9  
Sun Performance Library 9  
File System: ufs  
System State: Multi-User

## Notes/Tuning Information

### Compiler invocation:

C: cc  
F90: f90  
F77: f90

### Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
F90: -fast -xipo=2 with ONESTEP=yes and feedback

### Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1  
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6  
-Qoption iropt -Atile:skewp,-Ainline:cs=700  
(no feedback)  
172.mgrid: -fast -xipo=2



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Blade 1500 (1.5GHz)

SPECfp\_rate2000 = 14.8  
SPECfp\_rate\_base2000 = 13.1

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Dec-2004 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005

## Notes/Tuning Information (Continued)

```

173.applu:  -fast -xipo=2
            -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
            -Qoption iropt -Aujam:inner=g
177.mesa:   -fast -xipo=2 -xalias_level=strong -xrestrict
            -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art:    -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.quake:  -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ammp:   -fast -xarch=v9b -xipo=2 -xalias_level=std -lmopt -lm
189.lucas:  basepeak=yes
191.fma3d:  -fast -xipo=2 -stackvar -xprefetch_level=3
            -Qoption iropt -Apf:pdl=1
200.sixtrack: -xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2 -xprefetch=no
301.apsi:   -fast -xcrossfile

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```