



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL585 (AMD Opteron (TM) 852)

SPECfp_rate2000 = 82.2
SPECfp_rate_base2000 = 75.9

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	93.8	79.2	4	79.1	93.9
171.swim	4	143	101	4	143	101
172.mgrid	4	114	73.0	4	106	78.9
173.applu	4	133	73.2	4	115	84.8
177.mesa	4	72.5	89.5	4	65.8	98.7
178.galgel	4	107	126	4	98.3	137
179.art	4	134	90.2	4	96.2	125
183.equake	4	98.3	61.4	4	98.2	61.4
187.facerec	4	102	86.3	4	95.8	92.0
188.amp	4	155	65.9	4	150	68.0
189.lucas	4	112	82.9	4	111	83.5
191.fma3d	4	149	65.5	4	144	67.8
200.sixtrack	4	149	34.2	4	140	36.4
301.apsi	4	162	74.4	4	160	75.5

Hardware

CPU: AMD Opteron (TM) 852
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16x2048MB PC2700 CL2.5
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 for AMD64
 SuSE kernel 2.6.5-7.97-smp
 Compiler: PathScale EKO Compiler Suite, Release 1.4
 AMD Core Math Library 2.5.1
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex
Portability flags:
  178.galgel: -fixedform
Peak tuning:
  168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
               -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3 -TENV:X=4
               +FDO
               loader: -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
                       -INLINE:aggressive=on
  171.swim: -Ofast -LNO:fusion=2
  172.mgrid: -O3 -LNO:fusion=2:blocking=off
               -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3 -CG:gcm=off:cflow=off
  173.applu: -Ofast -CG:local_fwd_sched=on
               -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
               -OPT:ro=3 -TENV:X=3 -WOPT:val=2
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL585 (AMD Opteron (TM) 852)

SPECfp_rate2000 = 82.2
SPECfp_rate_base2000 = 75.9

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel:    -Ofast -OPT:fast_complex -CG:use_movlpd=on +ACML
179.art:       -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.equake:    -Ofast -WOPT:mem_opnds=on +FDO
  Note:        The configuration file contains peak optimization flags for 183.equake that are
                not invoked due to a syntax error. The options invoked during compilation
                are correctly described in the notes above.
187.facerec:   -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
                -LNO:fusion=2 +FDO
  loader:      -IPA:plimit=1800
188.ammpeg:    -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
                -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
189.lucas:     -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
                -WOPT:mem_opnds=on:retype_expr=on +FDO
  loader:      -IPA:pu_reorder=1
200.sixtrack:  -Ofast -CG:load_exe=1 +FDO
301.apsi:      -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
BIOS Configuration Notes
Node Interleaving is Disabled

```