



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION
I2X2 (1.6GHz Itanium 2 processor)

SPECfp_rate2000 = 44.0

SPECfp_rate_base2000 = 44.0

SPEC license #: 2697 | Tested by: ION | Test date: Jan-2005 | Hardware Avail: May-2004 | Software Avail: Dec-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	93.1	39.9	2	93.1	39.9
171.swim	2	152	47.4	2	152	47.4
172.mgrid	2	139	30.0	2	139	30.0
173.applu	2	62.0	78.6	2	62.0	78.6
177.mesa	2	115	28.3	2	115	28.3
178.galgel	2	56.8	118	2	56.8	118
179.art	2	21.1	286	2	21.1	286
183.equake	2	69.8	43.2	2	69.8	43.2
187.facerec	2	139	31.8	2	139	31.8
188.amp	2	158	32.2	2	158	32.2
189.lucas	2	179	25.9	2	179	25.9
191.fma3d	2	175	27.8	2	175	27.8
200.sixtrack	2	69.8	36.6	2	69.8	36.6
301.apsi	2	290	20.8	2	290	20.8

Hardware

CPU: Intel Itanium 2 processor
 CPU MHz: 1596
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: No
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (I+D) (on chip) per CPU
 L3 Cache: 3072KB (I+D) (on chip) per CPU
 Other Cache: N/A
 Memory: 8 GB (8x1GB DDR266, 2.5-3-3 DIMMS)
 Disk Subsystem: 1x36GB SCSI (Seagate Cheetah 15k rpm)
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux AS 3 Update 4, 2.4.21-27.EL, IPF
 Compiler: Intel(R) Fortran Compiler for Linux 8.1, IPF (Build 20041123)
 Intel(R) C Compiler for Linux 8.1, IPF (Build 20041123)
 MicroQuill SmartHeap library 7.01, IPF
 File System: ext3
 System State: Multi-user, run level 3

Notes/Tuning Information

Tested by ION Computer Systems

Baseline optimization flags:

C programs: -fast -IPF_fp_relaxed -ansi_alias +FDO
 Fortran programs: -fast -IPF_fp_relaxed +FDO

FP Peak optimization flags:

168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: basepeak=yes
 177.mesa: basepeak=yes



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION
I2X2 (1.6GHz Itanium 2 processor)

SPECfp_rate2000 = 44.0

SPECfp_rate_base2000 = 44.0

SPEC license #: 2697 | Tested by: ION | Test date: Jan-2005 | Hardware Avail: May-2004 | Software Avail: Dec-2004

Notes/Tuning Information (Continued)

```
178.galgel: basepeak=yes
179.art: basepeak=yes
183.equake: basepeak=yes
187.facerec: basepeak=yes
188.amp: basepeak=yes
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes
```

Portability Flags:
178.galgel: -FI