



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell Inc.
PowerEdge 1800SC (3.6Ghz Intel Xeon)

SPECint_rate2000 = 38.2
SPECint_rate_base2000 = 37.7

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Jan-2005 | Hardware Avail: Feb-2005 | Software Avail: Oct-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	119	27.3	2	119	27.2
175.vpr	2	120	27.1	2	120	27.1
176.gcc	2	56.2	45.4	2	56.2	45.4
181.mcf	2	113	36.8	2	113	36.8
186.crafty	2	74.8	31.0	2	74.5	31.1
197.parser	2	124	33.7	2	124	33.7
252.eon	2	58.3	51.8	2	58.0	52.0
253.perlbnk	2	99.2	42.1	2	87.0	48.0
254.gap	2	65.2	39.2	2	65.2	39.2
255.vortex	2	71.2	61.9	2	71.0	62.1
256.bzip2	2	121	28.8	2	120	28.9
300.twolf	2	168	41.4	2	166	41.8

Hardware

CPU: Intel Xeon (3.6Ghz, 2MB L2, 800MHz system bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB (dual-ranked) ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 18GB 15000RPM SCSI
Other Hardware: None

Software

Operating System: Windows 2003 Server, Standard Edition
Compiler: Intel C/C++ Compiler 8.1 (20041019Z)
Intel Fortran Compiler 8.1 (20041019Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 7.1
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved src.alt stdcpp
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -QxP -Qansi_alias +FDO
C++: -QxP -Qipo -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast -QxP -Qansi_alias -Oa +FDO
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -QxP -Oa +FDO shlW32M.lib
197.parser: basepeak=yes
252.eon: -fast -QxP +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell Inc.
PowerEdge 1800SC (3.6Ghz Intel Xeon)

SPECint_rate2000 = 38.2
SPECint_rate_base2000 = 37.7

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Jan-2005 | Hardware Avail: Feb-2005 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -QxP -Qansi_alias +FDO shlw32M.lib
254.gap:      basepeak=yes
255.vortex   -fast -QxP +FDO
256.bzip2:   -fast -QxP -Qunroll11 -Oa +FDO
300.twolf:   -fast -QxP +FDO shlw32M.lib
```