



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V20z

SPECint_rate2000 = 40.4
SPECint_rate_base2000 = 36.2

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Feb-2005 Hardware Avail: Apr-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	90.3	36.0	2	90.6	35.9
175.vpr	2	113	28.7	2	111	29.3
176.gcc	2	62.1	41.1	2	62.8	40.7
181.mcf	2	259	16.1	2	157	26.5
186.crafty	2	45.3	51.2	2	44.2	52.5
197.parser	2	153	27.2	2	126	33.2
252.eon	2	53.6	56.3	2	49.3	61.2
253.perlbnk	2	106	39.6	2	94.7	44.1
254.gap	2	67.7	37.7	2	65.8	38.8
255.vortex	2	75.7	58.2	2	68.3	64.6
256.bzip2	2	106	33.0	2	106	33.0
300.twolf	2	213	32.6	2	164	42.5

Hardware

CPU: AMD Opteron (TM) 252
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8GB (8x1GB, PC3200 CL3 DDR)
 Disk Subsystem: SCSI, 73GB, 10K RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 9
 Compiler: PathScale EKOPath Compiler Suite, Release 2.0
 File System: Linux/ext3
 System State: Multi-user, Run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags and Alternate Source:

176.gcc : srcalt=64bitgcc
 186.crafty : -DLINUX_i386
 252.eon : -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt=fmax_errno
 253.perlbnk : -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap : -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
 -DSPEC_CPU2000_LP64
 255.vortex : -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip : -O3 -ipa -m3dnow -WOPT:val=0 +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V20z

SPECint_rate2000 = 40.4
SPECint_rate_base2000 = 36.2

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Feb-2005 | Hardware Avail: Apr-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

175.vpr      : -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000 -INLINE:aggressive=on
              -IPA:space=300:plimit=10000:callee_limit=5000:linear=on +FDO
176.gcc      : -O3 -ipa -OPT:goto=off +FDO
181.mcf      : -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty   : -O3 -OPT:goto=off +FDO
197.parser   : -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon      : -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
              -TENV:X=4:frame_pointer=off -fno-exceptions
              -LNO:fu=10:full_unroll_outer=on -IPA:plimit=4000 +FDO
253.perlbnk  : -Ofast -OPT:transform_to_memlib=off -IPA:plimit=10000 +FDO
254.gap      : -Ofast -WOPT:aggstr=0 +FDO
255.vortex   : -Ofast -OPT:goto=off -IPA:plimit=1800 -CG:p2align=on +FDO
256.bzip2    : basepeak = true
300.twolf    : -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO

```

Note: The config file requested the vortex "closed_files" srcalt, but that srcalt was not in fact installed, so it was not used.
Default BIOS setting was used.