



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E6900 (16 processor)

SPECint_rate2000 = 249
SPECint_rate_base2000 = 223

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	32	298	175	32	262	198
175.vpr	32	259	201	32	254	205
176.gcc	32	219	186	32	172	238
181.mcf	32	301	222	32	257	260
186.crafty	32	156	238	32	126	294
197.parser	32	319	210	32	284	235
252.eon	32	153	316	32	150	321
253.perlbnk	32	277	242	32	252	265
254.gap	32	327	125	32	257	159
255.vortex	32	179	393	32	172	410
256.bzip2	32	222	250	32	215	259
300.twolf	32	504	221	32	486	229

Hardware

CPU: UltraSPARC IV
CPU MHz: 1350
FPU: Integrated
CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip
CPU(s) orderable: 4, 8, 12, 16, 20, 24 (order by number of chips)
Parallel: No
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)
L3 Cache: None
Other Cache: None
Memory: 128GB 16-way interleaved
Disk Subsystem: Sun StorEdge S1 Disk Array (2x36GB)
Sun StorEdge 6120 Array (14x73GB)
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Sun Studio 10
File System: ufs (default ufs logging on with Solaris 10)
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=30,
-Qeps:do_spec_load=1
175.vpr: -fast -xalias_level=std -xipo=2 -Wc,-Qeps:enabled=1,
-Qeps:rp_filtering_margin=100,-Qeps:do_spec_load=1 -lmopt -lm
176.gcc: -fast -xipo=2 -l12amm
181.mcf: -fast -xipo=2 -xprefetch_level=2 -Wc,-Qeps:enabled=1



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E6900 (16 processor)

SPECint_rate2000 = 249
SPECint_rate_base2000 = 223

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Jan-2005 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
            Feedback adds -xlinkopt in PASS2
197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible
253.perlbnk: -fast -xipo=2 -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -W2,-Abcopy -xvector
            -xprefetch_level=3
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enable=1
            -W2,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32
            -Wc,-Qpeep-Sh0 -W2,-crit -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1 -xsafe=mem -Qeps:rp_filtering_margin=99
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
            srcalt = fmax_errno
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

The system was configured with multiple file systems.
The O/S was installed on one disk of the Sun StorEdge S1
Disk Array (ufs, ufs w/logging). The benchmark was run on
the Sun StorEdge 6120 Array, using H/W Raid 5 and ufs with
ufs logging file system.