



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL380 G4 (3.6GHz, Intel Xeon)

SPECint\_rate2000 = 37.1  
SPECint\_rate\_base2000 = 36.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2005 Hardware Avail: Mar-2005 Software Avail: Feb-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	119	27.3	2	120	27.1
175.vpr	2	127	25.6	2	124	26.3
176.gcc	2	56.6	45.1	2	56.6	45.1
181.mcf	2	127	32.9	2	127	32.9
186.crafty	2	74.7	31.1	2	74.7	31.1
197.parser	2	125	33.5	2	124	33.6
252.eon	2	74.0	40.8	2	61.5	49.0
253.perlbnk	2	96.2	43.4	2	95.1	43.9
254.gap	2	69.6	36.7	2	69.5	36.7
255.vortex	2	66.4	66.4	2	66.2	66.6
256.bzip2	2	125	27.9	2	124	28.2
300.twolf	2	169	41.2	2	169	41.2

### Hardware

CPU: Intel Xeon (3.6GHz, 2MB L2, 800MHz bus)  
CPU MHz: 3600  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12K micro-ops I + 16KBD on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x1024MB PC2-3200  
Disk Subsystem: 1x18.2GB 15K Ultra320 SCSI  
Other Hardware:

### Software

Operating System: Windows Server 2003 Standard (Build 3790)  
Compiler: Intel C++ Compiler 8.1 Build 20040802Z  
Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.0  
File System: NTFS  
System State: Default

## Notes/Tuning Information

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -GX -GR

Portability flags:

176.gcc: -Dalloca=\_alloca /F10000000

186.crafty: -DNT\_i386

253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT

254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

Peak tuning:

164.gzip: -ipo -Oa +FDO ONESTEP=yes shlw32M.lib

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -QxP -O2 -Qipo +FDO

253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL380 G4 (3.6GHz, Intel Xeon)

SPECint\_rate2000 = 37.1  
SPECint\_rate\_base2000 = 36.4

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Feb-2005 | Hardware Avail: Mar-2005 | Software Avail: Feb-2005

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO ONESTEP=yes shlw32M.lib  
300.twolf: -fast -O3 +FDO shlw32M.lib  
BIOS Configuration Notes  
Hyper-Threading Technology disabled