



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX150 S3, Intel Pentium 4 560J processor

SPECint2000 = 1581
SPECint_base2000 = 1581

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: May-2005 Hardware Avail: Jan-2005 Software Avail: Mar-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	116	1203	116	1203	[Bar chart]			
175.vpr	1400	143	978	143	978	[Bar chart]			
176.gcc	1100	57.4	1916	57.4	1916	[Bar chart]			
181.mcf	1800	135	1336	135	1336	[Bar chart]			
186.crafty	1000	74.9	1335	74.9	1335	[Bar chart]			
197.parser	1800	131	1374	131	1374	[Bar chart]			
252.eon	1300	57.4	2264	57.4	2264	[Bar chart]			
253.perlbnk	1800	88.0	2045	88.0	2045	[Bar chart]			
254.gap	1100	58.0	1897	58.0	1897	[Bar chart]			
255.vortex	1900	71.8	2645	71.8	2645	[Bar chart]			
256.bzip2	1500	137	1091	137	1091	[Bar chart]			
300.twolf	3000	172	1744	172	1744	[Bar chart]			

Hardware

CPU: Intel Pentium 4 560J processor (3.60 GHz, 800 MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024 MB DDR-RAM PC-3200U
Disk Subsystem: Fujitsu MAS3367NC (SCSI U320 15 krpm)
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ Compiler 8.1 Build 20050405Z
Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries)
SmartHeap Library Version 6.03a from http://www.microquill.com
File System: NTFS
System State: default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: Approved srcalt stdcpp is used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlW32M.lib
for C++ programs: -fast -Qcxx_features +FDO

Peak tuning flags

same as baseline (basepeak=yes set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX150 S3, Intel Pentium 4 560J processor

SPECint2000 = 1581

SPECint_base2000 = 1581

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2005 | Hardware Avail: Jan-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>