



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECint_rate2000 = 42.3
SPECint_rate_base2000 = 38.4

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Aug-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	96.0	33.8	2	93.4	34.8
175.vpr	2	102	31.7	2	94.3	34.4
176.gcc	2	57.6	44.3	2	57.2	44.6
181.mcf	2	167	25.0	2	155	27.0
186.crafty	2	59.6	38.9	2	41.0	56.6
197.parser	2	126	33.2	2	125	33.4
252.eon	2	47.6	63.3	2	43.6	69.2
253.perlbnk	2	98.7	42.3	2	93.1	44.9
254.gap	2	76.1	33.6	2	68.9	37.0
255.vortex	2	78.9	55.9	2	62.2	70.9
256.bzip2	2	111	31.3	2	104	33.4
300.twolf	2	164	42.4	2	157	44.3

Hardware

CPU: AMD Opteron (TM) 254
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1,2 (order by # of chips)
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16GB (8x2GB, PC3200 CL3 DDR SDRAM ECC Registered)
 Disk Subsystem: SAS, 36GB, 10K RPM
 Other Hardware: None

Software

Operating System: Solaris 10 3/05 HW1
 Compiler: Sun Studio 11
 File System: ufs
 System State: Multi-user

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
fdo_pre0: rm -rf ./feedback.profile

Integer base flags:

Base tuning for C programs : -fast -xcrossfile -xalias_level=std +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -xcrossfile -xarch=amd64 +FDO ONESTEP=yes

Integer peak flags:

ONESTEP=yes +FDO for all benchmarks

164.gzip: -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign
 175.vpr: -fast -xpagesize=2m -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign -lmopt -lm
 176.gcc: -fast -xipo=2 -Wd,-iropt-prof -xalias_level=strong -xrestrict
 181.mcf: -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign
 186.crafty: -fast -xrestrict -xipo=2 -xprefetch -xarch=amd64 -xpagesize=2m



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4200

SPECint_rate2000 = 42.3
SPECint_rate_base2000 = 38.4

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Aug-2005 | Hardware Avail: Oct-2005 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

-M /usr/lib/ld/map.bssalign -Wd,-iropt-prof -W2,-Ashort_ldst:ldld
-W2,-Ainline:rs=50
197.parser: -fast -xpagesize=2m -xipo=2 -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign
252.eon: -fast -xipo=2 -qoption CC -iropt-prof -xvector -qoption iropt -Abcopy -xalias_level
-xarch=amd64 -xrestrict -Qoption ube -xcallee=yes -xregs=frameptr
253.perlbnk: -fast -xcrossfile -M /usr/lib/ld/map.bssalign -lbsdmalloc
254.gap: -fast -xipo=2 -Wd,-iropt-prof -xvector -W2,-Abcopy -lbsdmalloc -xprefetch
-W2,-Ainline:cp=5:rs=1300:irs=3300:inc=100 -W2,-Arestrict_g
255.vortex: -fast -xipo=2 -Wd,-iropt-prof -lbsdmalloc -xrestrict -xprefetch -M /usr/lib/ld/map.bssalign
256.bzip2: -fast -xpagesize=2m -xcrossfile -xarch=sse2 -Xc -M /usr/lib/ld/map.bssalign -lbsdmalloc
300.twolf: -fast -xipo=2 -Wd,-iropt-prof -xrestrict -M /usr/lib/ld/map.bssalign

```

Portability:

```

186.crafty: -DUNIX -DHAS_LONGLONG -DLITTLE_ENDIAN_ARCH
252.eon: -DFMAX_IS_DOUBLE -DSPEC_CPU2000_LP64 -DUSE_STRERROR
253.perlbnk: -DSPEC_CPU2000_SOLARIS_X86
254.gap: -DSYS_IS_USG -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

```

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind

Default BIOS setting was used

This result was measured on Sun Fire X4100;
Sun Fire X4100 and Sun Fire X4200 are electronically equivalent.