



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire X2100

SPECint2000 = 1815  
SPECint\_base2000 = 1651

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Aug-2005 Hardware Avail: Nov-2005 Software Avail: Nov-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	95.2	1470	93.0	1506	[Bar chart showing ratio bars for 164.gzip]			
175.vpr	1400	101	1381	95.2	1470	[Bar chart showing ratio bars for 175.vpr]			
176.gcc	1100	60.1	1831	59.4	1850	[Bar chart showing ratio bars for 176.gcc]			
181.mcf	1800	176	1022	166	1085	[Bar chart showing ratio bars for 181.mcf]			
186.crafty	1000	59.0	1695	40.6	2465	[Bar chart showing ratio bars for 186.crafty]			
197.parser	1800	125	1443	124	1451	[Bar chart showing ratio bars for 197.parser]			
252.eon	1300	47.2	2752	43.1	3014	[Bar chart showing ratio bars for 252.eon]			
253.perlbnk	1800	97.5	1846	91.8	1961	[Bar chart showing ratio bars for 253.perlbnk]			
254.gap	1100	78.5	1401	69.3	1587	[Bar chart showing ratio bars for 254.gap]			
255.vortex	1900	76.6	2481	60.8	3127	[Bar chart showing ratio bars for 255.vortex]			
256.bzip2	1500	111	1346	106	1415	[Bar chart showing ratio bars for 256.bzip2]			
300.twolf	3000	161	1859	154	1944	[Bar chart showing ratio bars for 300.twolf]			

### Hardware

CPU: AMD Opteron (TM) 154  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4GB (4x1GB, PC3200 CL3 DDR SDRAM)  
 Disk Subsystem: SATA, 80GB, 10K RPM  
 Other Hardware: None

### Software

Operating System: Solaris 10 3/05 HW1  
 Compiler: Sun Studio 11  
 File System: ufs  
 System State: Multi-user

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback  
fdo\_pre0: rm -rf ./feedback.profile

Integer base flags:

Base tuning for C programs : -fast -xcrossfile -xalias\_level=std +FDO ONESTEP=yes  
Base tuning for C++ programs: -fast -xcrossfile -xarch=amd64 +FDO ONESTEP=yes

Integer peak flags:

ONESTEP=yes +FDO for all benchmarks

164.gzip: -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign  
 175.vpr: -fast -xpagesize=2m -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign -lmopt -lm  
 176.gcc: -fast -xipo=2 -Wd,-iropt-prof -xalias\_level=strong -xrestrict  
 181.mcf: -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign  
 186.crafty: -fast -xrestrict -xipo=2 -xprefetch -xarch=amd64 -xpagesize=2m



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire X2100

SPECint2000 =	1815
SPECint_base2000 =	1651

SPEC license #:	6	Tested by:	Sun Microsystems, Santa Clara	Test date:	Aug-2005	Hardware Avail:	Nov-2005	Software Avail:	Nov-2005
-----------------	---	------------	-------------------------------	------------	----------	-----------------	----------	-----------------	----------

## Notes/Tuning Information (Continued)

```

-M /usr/lib/ld/map.bssalign -Wd,-iropt-prof -W2,-Ashort_ldst:ldld
-W2,-Ainline:rs=50
197.parser: -fast -xpagesize=2m -xipo=2 -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign
252.eon: -fast -xipo=2 -qoption CC -iropt-prof -xvector -qoption iropt -Abcopy -xalias_level
-xarch=amd64 -xrestrict -Qoption ube -xcallee=yes -xregs=frameptr
253.perlbnk: -fast -xcrossfile -M /usr/lib/ld/map.bssalign -lbsdmalloc
254.gap: -fast -xipo=2 -Wd,-iropt-prof -xvector -W2,-Abcopy -lbsdmalloc -xprefetch
-W2,-Ainline:cp=5:rs=1300:irs=3300:inc=100 -W2,-Arestrict_g
255.vortex: -fast -xipo=2 -Wd,-iropt-prof -lbsdmalloc -xrestrict -xprefetch -M /usr/lib/ld/map.bssalign
256.bzip2: -fast -xpagesize=2m -xcrossfile -xarch=sse2 -Xc -M /usr/lib/ld/map.bssalign -lbsdmalloc
300.twolf: -fast -xipo=2 -Wd,-iropt-prof -xrestrict -M /usr/lib/ld/map.bssalign

```

### Portability:

```

186.crafty: -DUNIX -DHAS_LONGLONG -DLITTLE_ENDIAN_ARCH
252.eon: -DFMAX_IS_DOUBLE -DSPEC_CPU2000_LP64 -DUSE_STRERROR
253.perlbnk: -DSPEC_CPU2000_SOLARIS_X86
254.gap: -DSYS_IS_USG -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

```

### Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"

### Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPU using submit=pbind

Default BIOS setting was used