



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Tomcat K8E (S2865), AMD Opteron (TM) 180

SPECint_rate2000 = 37.5
SPECint_rate_base2000 = 35.0

SPEC license #: 49 | Tested by: AMD, Austin TX | Test date: Aug-2005 | Hardware Avail: Nov-2005 | Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	107	30.4	2	107	30.4
175.vpr	2	112	29.1	2	108	29.9
176.gcc	2	63.7	40.1	2	62.7	40.7
181.mcf	2	242	17.3	2	189	22.1
186.crafty	2	63.7	36.4	2	57.8	40.2
197.parser	2	121	34.5	2	121	34.5
252.eon	2	58.6	51.5	2	50.4	59.8
253.perlbnk	2	111	37.7	2	111	37.7
254.gap	2	68.8	37.1	2	68.8	37.1
255.vortex	2	77.0	57.2	2	69.7	63.2
256.bzip2	2	126	27.7	2	123	28.4
300.twolf	2	183	38.0	2	155	44.9

Hardware

CPU: AMD Opteron (TM) 180 (939-pin)
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: no
Primary Cache: 64KBI + 64KBD/core
Secondary Cache: 1024KB (I+D)/core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x512 MB, DDR400 CL2
Disk Subsystem: SATA, Western Digital WD740GD, 74 GB 10000 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition SP1
Compiler: Intel C++ 8.0 build 20040415Z for IA32
Microsoft Visual Studio .NET 7.0.9466 (libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: default

Notes/Tuning Information

shlw32M.lib is the SmartHeap library V7.0 from MicroQuill www.microquill.com
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -fast -arch:SSE2 -Oi- +FDO

Baseline C++: -fast -arch:SSE2 -GX -GR

Peak Tuning:

164.gzip: basepeak=yes
175.vpr: -fast -arch:SSE2 +FDO
-Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
176.gcc: -fast -arch:SSE2 +FDO -Oi- -Qunroll3
181.mcf: -fast -QaxN +FDO
186.crafty: -fast -arch:SSE2 +FDO
197.parser: -arch:SSE2 +FDO -Oi- -Qipo
252.eon: -fast -arch:SSE2 +FDO -Qansi_alias
-Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN Tomcat K8E (S2865), AMD Opteron (TM) 180

SPECint_rate2000 = 37.5
SPECint_rate_base2000 = 35.0

SPEC license #: 49 | Tested by: AMD, Austin TX | Test date: Aug-2005 | Hardware Avail: Nov-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
253.perlbnk: basepeak=yes
254.gap:      basepeak=yes
255.vortex:   -fast -arch:SSE +FDO -Oi- shlw32m.lib
              -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
256.bzip2:    -fast -Qunroll2
300.twolf:    -fast -arch:SSE2 +FDO -Qunroll3 shlw32m.lib -Qansi_alias
The tested system can be built using a standard ATX case and an Antec
True 550W EPS12V power supply.
All memory slots populated on all CPU(s).
BIOS Version 2.01
'start /b /wait /affinity' command was used to bind CPU(s) to processes.
```