



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 346 (2.8 GHz Xeon, 2MB L2 Cache)

SPECint_rate2000 = 33.6

SPECint_rate_base2000 = 33.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	230	28.2	4	226	28.8
175.vpr	4	294	22.1	4	282	23.0
176.gcc	4	114	44.6	4	114	44.6
181.mcf	4	357	23.4	4	353	23.7
186.crafty	4	191	24.3	4	188	24.7
197.parser	4	258	32.4	4	257	32.5
252.eon	4	151	40.1	4	150	40.3
253.perlbnk	4	232	35.9	4	230	36.2
254.gap	4	137	37.3	4	134	38.1
255.vortex	4	157	56.2	4	157	56.2
256.bzip2	4	237	29.4	4	236	29.5
300.twolf	4	348	40.0	4	346	40.3

Hardware

CPU: Intel Xeon 2.8 (800 MHz system bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 512 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: srcalt=stdcpp
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO shlw32M.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: -fast +FDO shlw32M.lib
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: -fast +FDO
252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 346 (2.8 GHz Xeon, 2MB L2 Cache)

SPECint_rate2000 = 33.6

SPECint_rate_base2000 = 33.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Oa +FDO shlw32M.lib
254.gap:      -fast +FDO
255.vortex   -fast +FDO shlw32M.lib
256.bzip2:   -fast -Qunroll11 -Oa +FDO shlw32M.lib
300.twolf:   -fast +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib: MicroQuill SmartHeap Library 7.1
              www.microquill.com
```