



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 346 (2.8 GHz Xeon, 2MB L2 Cache)

SPECint_rate2000 = 17.7

SPECint_rate_base2000 = 17.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	228	14.2	2	224	14.5
175.vpr	2	284	11.5	2	271	12.0
176.gcc	2	113	22.5	2	113	22.5
181.mcf	2	226	18.5	2	225	18.6
186.crafty	2	184	12.6	2	186	12.5
197.parser	2	254	16.4	2	253	16.5
252.eon	2	150	20.2	2	149	20.2
253.perlbnk	2	235	17.8	2	233	17.9
254.gap	2	126	20.3	2	124	20.6
255.vortex	2	155	28.4	2	155	28.4
256.bzip2	2	228	15.3	2	228	15.3
300.twolf	2	347	20.1	2	346	20.1

Hardware

CPU: Intel Xeon 2.8 (800 MHz system bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 512 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO shlw32M.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: -fast +FDO shlw32M.lib
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: -fast +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Oa +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 346 (2.8 GHz Xeon, 2MB L2 Cache)

SPECint_rate2000 = 17.7

SPECint_rate_base2000 = 17.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

```
254.gap:      -fast +FDO
255.vortex    -fast +FDO shlw32M.lib
256.bzip2:    -fast -Qunroll1 -Oa +FDO shlw32M.lib
300.twolf:    -fast +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.1
              www.microquill.com
```