



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G4p (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 21.7

SPECfp_rate_base2000 = 21.5

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	121	30.7	2	121	30.7
171.swim	2	252	28.6	2	252	28.5
172.mgrid	2	212	19.7	2	217	19.3
173.applu	2	287	17.0	2	285	17.1
177.mesa	2	173	18.8	2	173	18.8
178.galgel	2	186	36.1	2	187	36.1
179.art	2	169	35.6	2	169	35.6
183.quake	2	114	26.5	2	94.7	31.8
187.facerec	2	175	25.2	2	176	25.1
188.amp	2	347	14.7	2	347	14.7
189.lucas	2	219	21.2	2	219	21.2
191.fma3d	2	280	17.4	2	280	17.4
200.sixtrack	2	255	10.0	2	254	10.0
301.apsi	2	350	17.2	2	350	17.2

Hardware

CPU: Intel Xeon (3.6GHz, 2MB L2, 800MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC2-3200
Disk Subsystem: 1x80.0GB 7.2k Serial ATA
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.1 Build 20050524Z)
Intel Fortran Compiler for 32-bit applications, (Version 8.1 Build 20050517Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning: -fast -Qansi_alias +FDO

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast -f77rtl +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: -fast +FDO ONESTEP=yes

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- -fpp +FDO ONESTEP=yes

188.amp: basepeak=1



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G4p (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 21.7
SPECfp_rate_base2000 = 21.5

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

189.lucas: -fast
191.fma3d: basepeak=1
200.sixtrack: -fast +FDO
301.apsi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology enabled