



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G4p (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 32.3
SPECfp_rate_base2000 = 31.5

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	71.6	51.8	2	71.7	51.8
171.swim	2	267	26.9	2	267	26.9
172.mgrid	2	171	24.4	2	171	24.4
173.applu	2	212	23.0	2	206	23.6
177.mesa	2	89.2	36.4	2	89.3	36.4
178.galgel	2	94.4	71.3	2	94.2	71.4
179.art	2	88.7	68.0	2	88.7	68.0
183.quake	2	106	28.3	2	78.9	38.2
187.facerec	2	123	35.9	2	123	35.8
188.amp	2	190	26.8	2	190	26.8
189.lucas	2	185	25.1	2	184	25.2
191.fma3d	2	197	24.7	2	197	24.7
200.sixtrack	2	170	15.0	2	170	15.0
301.apsi	2	223	27.1	2	223	27.1

Hardware

CPU: Intel Xeon (3.6GHz, 2MB L2, 800MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC2-3200
Disk Subsystem: 1x80.0GB 7.2k Serial ATA
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.1 Build 20050524Z)
Intel Fortran Compiler for 32-bit applications, (Version 8.1 Build 20050517Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smarheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning: -fast -Qansi_alias +FDO

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias

+FDO

171.swim: -fast

-f77rtl +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias

+FDO

173.applu: -fast -Qscalar_rep- -Qauto -f77rtl

+FDO ONESTEP=yes

177.mesa: -fast

+FDO ONESTEP=yes

178.galgel: -fast

+FDO ONESTEP=yes

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd

+FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- -fpp

+FDO ONESTEP=yes

188.amp: basepeak=1

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G4p (3.6GHz, Intel Xeon)

SPECfp_rate2000 = 32.3
SPECfp_rate_base2000 = 31.5

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

189.lucas: -fast
191.fma3d: basepeak=1
200.sixtrack: -fast +FDO
301.apsi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled