



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Supermicro X6DHR-3G2 Motherboard

SPECfp\_rate2000 = 33.3

SPECfp\_rate\_base2000 = 33.4

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	127	58.5	4	127	58.5
171.swim	4	531	27.1	4	532	27.1
172.mgrid	4	336	24.8	4	337	24.8
173.applu	4	379	25.7	4	373	26.1
177.mesa	4	166	39.2	4	166	39.2
178.galgel	4	250	53.9	4	249	54.0
179.art	4	289	41.7	4	289	41.7
183.quake	4	168	35.9	4	168	35.9
187.facerec	4	214	41.1	4	213	41.3
188.amp	4	383	26.7	4	393	26.0
189.lucas	4	353	26.3	4	353	26.3
191.fma3d	4	337	28.9	4	337	28.9
200.sixtrack	4	233	21.9	4	240	21.3
301.apsi	4	329	36.7	4	329	36.7

### Hardware

CPU: Intel Xeon Processor (3.80 GHz, 2MB L2, 800 MHz bus)  
CPU MHz: 3800  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Enabled)  
CPU(s) orderable: 1, 2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 x 2.0GB SMART DDR2 400MHz ECC  
Disk Subsystem: 1 X 250GB Western Digital WD2500JD-00GBB0 SATA HDD  
Other Hardware: N/A

### Software

Operating System: Windows Server 2003 EE w/SP1  
Compiler: Intel C++ and Fortran Compiler 9.0 Build 20050430Z (32-bit)  
Microsoft Visual Studio .Net 2003(for libraries)  
SmartHeap Library Version 7.4 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability:
178.galgel: -FI /F32000000
191.fmma3d approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo shlw32M.lib +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro  
X6DHR-3G2 Motherboard

SPECfp\_rate2000 = 33.3

SPECfp\_rate\_base2000 = 33.4

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

188. ammp: -fast -Oa +FDO shlw32M.lib

189. lucas: -fast -Qprefetch- +FDO

191. fma3d: basepeak=yes

200. sixtrack: -Qipo -QxP +FDO

301. apsi: -fast +FDO

New 32-bit Windows tools used, approved in May-2005

Tested system was built with SC813T-500 Chassis.

Product description located as of:

<http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHR-3G2.cfm>

The system bus runs at 800MHz