



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro X6DHP-TG Motherboard

SPECint2000 = 1735
SPECint_base2000 = 1740

SPEC license #01176 Tested by: Supermicro Test date: Oct-2005 Hardware Avail: Sep-2005 Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	113	1240	115	1219	
175.vpr	1400	120	1162	121	1161	
176.gcc	1100	52.9	2079	52.9	2079	
181.mcf	1800	105	1718	105	1718	
186.crafty	1000	72.5	1379	73.0	1369	
197.parser	1800	120	1501	120	1500	
252.eon	1300	55.1	2361	55.2	2354	
253.perlbmk	1800	80.4	2240	81.1	2221	
254.gap	1100	56.2	1958	56.2	1958	
255.vortex	1900	67.3	2823	67.3	2823	
256.bzip2	1500	116	1293	116	1295	
300.twolf	3000	157	1913	157	1914	

Hardware

CPU: Intel Xeon Processor (3.80 GHz, 2MB L2, 800 MHz bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology Disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6GB (6x1GB 2 X 1GB DDR 333 REG ECC)
Disk Subsystem: 1 X 40GB IDE
Other Hardware: N/A

Software

Operating System: Windows 2003 EE SP1
Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DHP-TG Motherboard

SPECint2000 =	1735
SPECint_base2000 =	1740

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

255.vortex basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
New 32-bit Windows tools used, approved in May-2005
Tested system was built with SC814+ Chassis.
Product description located as of:
<http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHP-TG.cfm>
The system bus runs at 800MHz