



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon 3.60 GHz

SPECint_rate2000 = 21.7
SPECint_rate_base2000 = 21.7

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	175	18.5	2	175	18.5
175.vpr	2	226	14.4	2	226	14.4
176.gcc	2	89.6	28.5	2	89.6	28.5
181.mcf	2	208	20.0	2	208	20.0
186.crafy	2	149	15.6	2	149	15.6
197.parser	2	205	20.4	2	205	20.4
252.eon	2	129	23.5	2	129	23.5
253.perlbnk	2	184	22.7	2	184	22.7
254.gap	2	99.4	25.7	2	99.4	25.7
255.vortex	2	127	34.6	2	127	34.6
256.bzip2	2	186	18.7	2	186	18.7
300.twolf	2	276	25.2	2	276	25.2

Hardware

CPU: 64-bit Intel Xeon processor 3.6GHz, 2MB L2, 800MHz system bus
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x512 MB DDRII-RAM PC2-3200R
Disk Subsystem: Fujitsu MAS3367NC (U320, 15krpm)
Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ Compiler 9.0
Build 20050722Z (for 32-bit applications)
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries)
SmartHeap Library Version 7.4
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: Approved srcalt stdcpp is used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32M.lib
for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=yes set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon 3.60 GHz

SPECint_rate2000 = 21.7
SPECint_rate_base2000 = 21.7

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>