



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S2, Intel Xeon processor 3.40GHz, 2MB L2

SPECfp\_rate2000 = 21.2

SPECfp\_rate\_base2000 = 21.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	128	29.0	2	128	29.0
171.swim	2	252	28.6	2	252	28.6
172.mgrid	2	228	18.4	2	228	18.4
173.applu	2	306	15.9	2	306	15.9
177.mesa	2	187	17.4	2	187	17.4
178.galgel	2	195	34.4	2	195	34.4
179.art	2	161	37.5	2	161	37.5
183.quake	2	85.6	35.2	2	85.6	35.2
187.facerec	2	182	24.2	2	182	24.2
188.amp	2	372	13.7	2	372	13.7
189.lucas	2	224	20.7	2	224	20.7
191.fma3d	2	284	17.2	2	284	17.2
200.sixtrack	2	257	9.92	2	257	9.92
301.apsi	2	354	17.0	2	354	17.0

### Hardware

CPU: Intel Xeon processor 3.40GHz, 2MB L2, 800MHz system bus  
CPU MHz: 3400  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip, per core  
Secondary Cache: 2048KB(I+D) on chip, per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x512 MB DDRII-RAM PC2-3200R  
Disk Subsystem: Seagate ST336753LC(U320 SCSI, 15krpm)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1  
Compiler: Intel C and Fortran Compiler 9.0  
Build 20050722Z (for 32-bit applications)  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries)  
SmartHeap Library Version 7.4  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

178.galgel: -FI /F32000000

### Base tuning flags

for Fortran programs: -fast -Qansi\_alias +FDO shlW32M.lib  
for C programs: -fast +FDO shlW32M.lib

### Peak tuning flags

same as baseline (basepeak=yes set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX200 S2, Intel Xeon processor 3.40GHz, 2MB L2

SPECfp\_rate2000 = 21.2

SPECfp\_rate\_base2000 = 21.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

## Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>