



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel 100, Intel Pentium 4 processor 630, 3GHz

SPECint_rate2000 = 17.2

SPECint_rate_base2000 = 17.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	1	139	11.6	1	139	11.6
175.vpr	1	135	12.0	1	135	12.0
176.gcc	1	61.8	20.6	1	61.8	20.6
181.mcf	1	95.7	21.8	1	95.7	21.8
186.crafy	1	90.2	12.9	1	90.2	12.9
197.parser	1	143	14.6	1	143	14.6
252.eon	1	73.3	20.6	1	73.3	20.6
253.perlbnk	1	100	20.8	1	100	20.8
254.gap	1	66.7	19.1	1	66.7	19.1
255.vortex	1	74.5	29.6	1	74.5	29.6
256.bzip2	1	130	13.4	1	130	13.4
300.twolf	1	197	17.7	1	197	17.7

Hardware

CPU: Intel Pentium 4 processor 630, 3GHz, 800MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip
 Secondary Cache: 2 MB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2 GB DDR2-SDRAM PC2-4200
 Disk Subsystem: Seagate ST3160023AS (SATA, 7.2krpm)
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
 Compiler: Intel C++ Compiler 9.0
 Build 20050722Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 7.4
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafy: -DNT_i386
 252.eon: Approved srcalt stdcpp is used
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
 for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=yes set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel 100, Intel Pentium 4 processor 630, 3GHz

SPECint_rate2000 = 17.2

SPECint_rate_base2000 = 17.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>