



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E20K (8 processor)

SPECint_rate2000 = 170

SPECint_rate_base2000 = 145

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	16	213	122	16	192	135
175.vpr	16	188	138	16	182	143
176.gcc	16	232	88.1	48	345	178
181.mcf	16	257	130	48	649	154
186.crafty	16	97.1	191	16	88.5	210
197.parser	16	245	136	16	211	158
252.eon	16	126	191	16	117	206
253.perlbnk	16	194	172	16	186	179
254.gap	16	270	75.5	48	577	106
255.vortex	16	126	280	16	117	302
256.bzip2	16	180	155	16	177	158
300.twolf	16	353	158	16	319	175

Hardware

CPU: UltraSPARC IV+
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 16 cores, 8 chips, 2 cores/chip
 CPU(s) orderable: 4-36 (order by number of chips, groups of 4)
 Parallel: No
 Primary Cache: 64KBI+64KBD per core on chip (128KBI+128KBD on chip)
 Secondary Cache: 2MB(I+D) per chip (on chip)
 L3 Cache: 32MB(I+D) per chip (off chip)
 Other Cache: None
 Memory: 64GB 16-way interleaved
 Disk Subsystem: Sun StorEdge D240 Media Tray (2x73GB)
 Sun StorEdge 6120 Array (14x73GB)
 Other Hardware: None

Software

Operating System: Solaris 10
 Compiler: Sun Studio 11
 File System: ufs (default ufs logging on with Solaris 10)
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes for all benchmarks
Profile feedback used for those marked with +FDO

164.zip: -x04 -xbuiltin=%all -xtarget=native -xalias_level=std
 -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=30,
 -Qeps:do_spec_load=1 +FDO
 175.vpr: -fast -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,
 -Qeps:rp_filtering_margin=30 -xipo=2 -xpagesize_stack=8K
 -lmopt -lm +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E20K (8 processor)

SPECint_rate2000 = 170
SPECint_rate_base2000 = 145

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

176.gcc: -fast -xipo=2 -Wc,-Qicache-chbab=1 -Wc,-Qeps:enabled=1
        -Qeps:ws=32 -Wc,-Qdepgraph-early_cross_call=1
        -Wc,-Qms_pipe-pref_prolog -ll2amm +FDO
181.mcf: -fast -xipo=2 -xprefetch_level=2
186.crafty: -fast -xpagesize=8k -xipo=2 -xalias_level=strong
        -W2,-Ashort_ldst -xinline= -xprefetch -xrestrict
        +FDO (-xlinkopt during pass2)
197.parser: -fast -xipo=2 -xalias_level=strong -Wc,Qgsched-T6
        -Wc,-Qipa:valueprediction -Wc,-Qms_pipe-prefstrong=0,
        -Qlp-pt=weak +FDO
252.eon: -fast -xipo=2 -xalias_level=compatible -Qoption cg
        -Qeps:enabled=1 -xvector -Qoption iropt -Abcopy -xunroll=16
        +FDO
253.perlbnk: -fast -xipo -Wc,-Qeps:enabled=1,-Qeps:ws=16 -xalias_level=std
        -xsafe=mem -Wc,-Qiselect-funcalign=128,-Qicache-chbab=1
        -Wc,-Qiselect-sw_pf_tbl_th=40,-Qeps:do_spec_load=1 +FDO
254.gap: -fast -W2,-Abcopy -xvector -xprefetch_level=3 +FDO
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enabled=1
        -W2,-Ainline:recursion=1:cs=400:irs=5000
        -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=64
        -Wc,-Qpeep-Sh0 -W2,-crit -xprefetch=latx:1.7 -fsimple=1
        -Wc,-Qiselect-sw_pf_tbl_th=30 -Wc,-Qicache-chbab=1
        -W2,-Ainline:inc=300 -ll2amm +FDO
256.bzip2: -fast -xipo=2 -xalias_level=strong -xrestrict
        -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1 +FDO
300.twolf: -fast -xalias_level=strong -xsafe=mem -xipo=2
        -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp -xinline= +FDO

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Portability:

```

176.gcc:  -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -DFMAX_IS_DOUBLE -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
        -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

The system was configured with multiple file systems.
The O/S was installed on one disk of the Sun StorEdge D240
Media Tray (ufs, ufs w/logging). The benchmark was run on
the Sun StorEdge 6120 Array, using H/W Raid 5 and ufs with
ufs logging file system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E20K (8 processor)

SPECint_rate2000 = 170

SPECint_rate_base2000 = 145

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Notes/Tuning Information (Continued)