



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Ultra 40

SPECfp2000 = 2505

SPECfp_base2000 = 2212

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Feb-2006 Hardware Avail: Jan-2006 Software Avail: Nov-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	52.7	3039	50.7	3155	
171.swim	3100	72.9	4252	65.9	4704	
172.mgrid	1800	50.1	3593	50.1	3593	
173.applu	2100	52.3	4017	49.7	4222	
177.mesa	1400	86.4	1621	66.6	2101	
178.galgel	2900	62.0	4678	62.2	4665	
179.art	2600	110	2358	110	2358	
183.earthquake	1300	73.0	1781	66.9	1942	
187.facerec	1900	60.8	3124	45.2	4206	
188.ammpp	2200	147	1502	149	1475	
189.lucas	2000	124	1615	124	1617	
191.fma3d	2100	106	1973	106	1975	
200.sixtrack	1100	310	354	140	783	
301.apsi	2600	122	2134	107	2440	

Hardware

CPU: AMD Opteron (TM) 254
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2 (order by number of chips)
Parallel: Yes
Primary Cache: 64KBI + 64KBD (on chip) per core
Secondary Cache: 1024KB (I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16GB (8x2GB, PC3200 CL3 DDR SDRAM ECC Registered)
Disk Subsystem: SATA,250GB,7200 RPM
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Sun Studio 11
File System: ufs
System State: Multi-user

Notes/Tuning Information

Compiler invocation:

C: cc
F90: f90
F77: f90

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
fdo_pre0: rm -rf ./feedback.profile

Floating point base flags:

F90: -fast -xautopar -xipo=2 -xarch=amd64
C: -fast -xcrossfile -xalias_level=std -xpagesize=2m

Floating point peak flags:

ONESTEP=yes for all benchmarks

168.wupwise: -fast -xautopar -xpad=common:3969 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xpagesize_heap=2m
171.swim: -fast -xpad=common:3969 -xipo=2 -xvector=simd -xprefetch_level=3 -Qoption iropt



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Ultra 40

SPECfp2000 = 2505

SPECfp_base2000 = 2212

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Feb-2006 | Hardware Avail: Jan-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

-Atile:skewp,-Ainline:cs=700 -xarch=amd64 -Qoption ube_ipa -inl_alt
-xpagesize_stack=2m
172.mgrid: basepeak=yes
173.applu: -fast -xautopar -unroll=5 -stackvar -xO4 -xipo=2 -xprefetch_level=3 -xarch=amd64a
          -qoption iropt -Rloop_dist -xpagesize_heap=2m
177.mesa: -fast -xautopar -xO4 -xipo=2 -Wd,-iropt-prof -xarch=amd64 -xalias_level=strong -xpagesize=2m +FDO
178.galgel: -fast -xipo=2 -xarch=amd64 -xprefetch_level=3
179.art: basepeak=yes
183.equake: -fast -xautopar -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m -lmopt -lm +FDO
187.facerec: -fast -xO4 -xipo=2 -xprefetch_level=3 -xpagesize=2m
            RM_SOURCES=cfftb.f90 cffti.f90 cfftf.f90
            EXTRALIBS=-xlic_lib=sunperf
188.amp: -fast -xautopar -xcache=64/32/4:1024/64/4 -xarch=sse2a -xO4 -xipo=2 -xarch=amd64a
          -xalias_level=std -xpagesize_heap=2m -lmopt -lm
189.lucas: -fast -xautopar -Qoption ube_ipa -inl_alt -xipo=2 -xarch=amd64 -xprefetch_level=3
191.fma3d: -fast -xautopar -xcache=64/32/4:1024/64/4 -xarch=sse2a -unroll=5 -fsimple=1 -xipo=2
          -xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m +FDO
200.sixtrack: -fast -xipo=2 -O -xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m
              -Qoption ld -M,/usr/lib/ld/map.bssalign +FDO
301.apsi: -fast -xO4 -xipo=2 -xprefetch_level=3 -xarch=amd64 -xpagesize=2m

```

Portability:

178.galgel: -fixed

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"
export PARALLEL=2

Default BIOS setting was used