



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN Thunder K8SD Pro (S2882-D), AMD Opteron (TM) 256

SPECint_rate2000 = 47.2

SPECint_rate_base2000 = 42.1

SPEC license #: 49 | Tested by: AMD Austin, Texas | Test date: Mar-2006 | Hardware Avail: Apr-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	77.8	41.8	2	77.5	41.9
175.vpr	2	98.2	33.1	2	95.3	34.1
176.gcc	2	54.8	46.6	2	55.2	46.2
181.mcf	2	232	18.0	2	144	28.9
186.crafty	2	37.9	61.2	2	37.0	62.7
197.parser	2	134	31.2	2	105	39.6
252.eon	2	42.5	71.0	2	36.3	83.0
253.perlbnk	2	91.1	45.9	2	79.5	52.5
254.gap	2	57.1	44.7	2	57.1	44.7
255.vortex	2	64.2	68.7	2	60.0	73.5
256.bzip2	2	91.2	38.1	2	91.2	38.1
300.twolf	2	186	37.3	2	146	47.6

Hardware

CPU: AMD Opteron (TM) 256
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512MB, DDR400 CL2 ECC Reg
 Disk Subsystem: SATA, 250 GB
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 9 SP3 (64-bit)
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3
 File System: Linux/ext3
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN Thunder K8SD Pro (S2882-D), AMD Opteron (TM) 256

SPECint_rate2000 = 47.2

SPECint_rate_base2000 = 42.1

SPEC license #: 49 | Tested by: AMD Austin, Texas | Test date: Mar-2006 | Hardware Avail: Apr-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

```
181.mcf:      -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:   -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:   -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
              -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
              -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk:  -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
255.vortex:   -Ofast -OPT:goto=off -CG:p2align=on
              -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2:    basepeak = true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

Corsair CMX512RE-3200LL (XMS3200REv2.1) memory used in Dual Channel configuration.
BIOS rev 3.06
The tested system can be assembled using a standard ATX case and an Antec True 550 watt EPS12V Power Supply.
taskset utility used to bind CPU(s) to processes.