



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire X4100

SPECint2000 = 1940  
SPECint\_base2000 = 1761

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2006 Hardware Avail: May-2006 Software Avail: Jan-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	89.4	1566	87.2	1605	[Bar chart showing runtime and ratio for 164.gzip]			
175.vpr	1400	97.0	1443	89.6	1563	[Bar chart showing runtime and ratio for 175.vpr]			
176.gcc	1100	53.9	2042	53.3	2066	[Bar chart showing runtime and ratio for 176.gcc]			
181.mcf	1800	162	1108	151	1194	[Bar chart showing runtime and ratio for 181.mcf]			
186.crafty	1000	55.5	1801	38.4	2601	[Bar chart showing runtime and ratio for 186.crafty]			
197.parser	1800	118	1520	117	1533	[Bar chart showing runtime and ratio for 197.parser]			
252.eon	1300	44.8	2904	40.3	3226	[Bar chart showing runtime and ratio for 252.eon]			
253.perlbnk	1800	92.4	1948	86.5	2082	[Bar chart showing runtime and ratio for 253.perlbnk]			
254.gap	1100	70.4	1562	64.7	1699	[Bar chart showing runtime and ratio for 254.gap]			
255.vortex	1900	73.2	2594	58.0	3274	[Bar chart showing runtime and ratio for 255.vortex]			
256.bzip2	1500	105	1422	98.7	1520	[Bar chart showing runtime and ratio for 256.bzip2]			
300.twolf	3000	154	1942	148	2025	[Bar chart showing runtime and ratio for 300.twolf]			

### Hardware

CPU: AMD Opteron (TM) 256  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1,2 (order by # of chips)  
Parallel: No  
Primary Cache: 64KBI + 64KBD (on chip) per core  
Secondary Cache: 1024KB (I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8GB (4x2GB, PC3200 CL3 DDR ECC Registered SDRAM)  
Disk Subsystem: SAS,36GB,10K RPM  
Other Hardware: None

### Software

Operating System: Solaris 10 1/06  
Compiler: Sun Studio 11  
File System: ufs  
System State: Multi-user

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback  
fdo\_pre0: rm -rf ./feedback.profile

Integer base flags:

Base tuning for C programs : -fast -xcrossfile -xalias\_level=std +FDO ONESTEP=yes  
Base tuning for C++ programs: -fast -xcrossfile -xarch=amd64 +FDO ONESTEP=yes

Integer peak flags:

ONESTEP=yes +FDO for all benchmarks

164.gzip: -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign  
175.vpr: -fast -xpagesize=2m -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign -lmopt -lm  
176.gcc: -fast -xipo=2 -Wd,-iropt-prof -xalias\_level=strong -xrestrict  
181.mcf: -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign  
186.crafty: -fast -xrestrict -xipo=2 -xprefetch -xarch=amd64 -xpagesize=2m  
-M /usr/lib/ld/map.bssalign -Wd,-iropt-prof -W2,-Ashort\_ldst:ldld



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire X4100

SPECint2000 =	1940
SPECint_base2000 =	1761

SPEC license #:	6	Tested by:	Sun Microsystems, Santa Clara	Test date:	Mar-2006	Hardware Avail:	May-2006	Software Avail:	Jan-2006
-----------------	---	------------	-------------------------------	------------	----------	-----------------	----------	-----------------	----------

## Notes/Tuning Information (Continued)

```

-W2,-Ainline:rs=50
197.parser: -fast -xpagesize=2m -xipo=2 -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign
252.eon: -fast -xipo=2 -qoption CC -iropt-prof -xvector -qoption iropt -Abcopy -xalias_level
        -xarch=amd64 -xrestrict -Qoption ube -xcallee=yes -xregs=frameptr
253.perlbnk: -fast -xcrossfile -M /usr/lib/ld/map.bssalign -lbsdmalloc
254.gap: -fast -xipo=2 -Wd,-iropt-prof -xvector -W2,-Abcopy -lbsdmalloc -xprefetch
        -W2,-Ainline:cp=5:rs=1300:irs=3300:inc=100 -W2,-Arestrict_g
255.vortex: -fast -xipo=2 -Wd,-iropt-prof -lbsdmalloc -xrestrict -xprefetch -M /usr/lib/ld/map.bssalign
256.bzip2: -fast -xpagesize=2m -xcrossfile -xarch=sse2 -Xc -M /usr/lib/ld/map.bssalign -lbsdmalloc
300.twolf: -fast -xipo=2 -Wd,-iropt-prof -xrestrict -M /usr/lib/ld/map.bssalign

```

### Portability:

```

186.crafty (base): -DSOLARIS_X86
186.crafty (peak): -DSOLARIS_X64
252.eon: -DSPEC_CPU2000_LP64 -DUSE_STRERROR
253.perlbnk: -DSPEC_CPU2000_SOLARIS_X86
254.gap: -DSYS_IS_USG -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

```

### Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"

System was tested in 1 chips configuration

Default BIOS setting was used

This result was measured on the Sun Fire X4200.  
Sun Fire X4100 and Sun Fire X4200 are electronically equivalent.