



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECint_rate2000 = 89.8
SPECint_rate_base2000 = 78.8

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2006 Hardware Avail: May-2006 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	77.7	83.6	4	77.3	84.0
175.vpr	4	111	58.4	4	103	63.1
176.gcc	4	57.2	89.3	4	57.2	89.3
181.mcf	4	323	25.9	4	180	46.4
186.crafty	4	37.7	123	4	36.6	127
197.parser	4	140	59.6	4	108	77.0
252.eon	4	41.5	145	4	36.2	167
253.perlbnk	4	93.2	89.6	4	81.9	102
254.gap	4	59.3	86.1	4	59.3	86.1
255.vortex	4	69.1	127	4	64.9	136
256.bzip2	4	98.6	70.6	4	98.6	70.6
300.twolf	4	201	69.4	4	152	91.4

Hardware

CPU: AMD Opteron (TM) 856
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2,4 (order by # of chips)
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16GB (8x2GB, PC3200 CL3 DDR ECC Registered SDRAM)
 Disk Subsystem: 2x72GB,SCSI,10K RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 9 SP3 (x86_64)
 Compiler: PathScale EKOPath(TM) Compiler Suite, Version 2.3
 File System: Linux/ext3
 System State: Multi-user, run level 3

Notes/Tuning Information

GENERAL:

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECint_rate2000 = 89.8
SPECint_rate_base2000 = 78.8

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Mar-2006 | Hardware Avail: May-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```
181.mcf:      -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:   -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:   -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
              -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
              -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk:  -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
255.vortex:   -Ofast -OPT:goto=off -CG:p2align=on
              -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2:    basepeak = true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

taskset utility used to bind CPU(s) to processes.

Default BIOS setting was used

Half memory slots populated on all CPU(s) in dual-channel configuration.