



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML570 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp2000 = **1534**
SPECfp_base2000 = **1527**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: May-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	58.0	2757	58.0	2758	[Bar chart showing ratio 2758]			
171.swim	3100	153	2028	153	2028	[Bar chart showing ratio 2028]			
172.mgrid	1800	142	1271	142	1271	[Bar chart showing ratio 1271]			
173.applu	2100	149	1407	149	1407	[Bar chart showing ratio 1407]			
177.mesa	1400	110	1278	109	1285	[Bar chart showing ratio 1285]			
178.galgel	2900	97.5	2975	97.5	2975	[Bar chart showing ratio 2975]			
179.art	2600	76.8	3387	76.8	3387	[Bar chart showing ratio 3387]			
183.earthquake	1300	57.7	2255	57.7	2255	[Bar chart showing ratio 2255]			
187.facerec	1900	151	1257	151	1256	[Bar chart showing ratio 1256]			
188.amp	2200	243	906	230	955	[Bar chart showing ratio 955]			
189.lucas	2000	146	1371	146	1375	[Bar chart showing ratio 1375]			
191.fma3d	2100	167	1257	167	1257	[Bar chart showing ratio 1257]			
200.sixtrack	1100	187	588	187	588	[Bar chart showing ratio 588]			
301.apsi	2600	232	1120	232	1120	[Bar chart showing ratio 1120]			

Hardware

CPU: Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16x2048MB PC2-3200 dual-rank
Disk Subsystem: 1x36GB SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for Fortran programs: -fast -Qansi_alias +FDO

Base tuning for C programs: -fast +FDO shlw32M.lib

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: basepeak=1

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: basepeak=1

179.art: basepeak=1

183.earthquake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes

188.amp: -fast -Qansi_alias +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML570 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp2000 = 1534
SPECfp_base2000 = 1527

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
189.lucas:      -fast
191.fma3d:      basepeak=1
200.sixtrack:   -fast                      +FDO
301.apsi:       basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```