



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3950 (2.5 GHz Xeon 7110N)

SPECint2000 = --
SPECint_base2000 = 1233

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Dec-2006 | Hardware Avail: Oct-2006 | Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	164	853		
175.vpr	1400	167	838		
176.gcc	1100	77.3	1424		
181.mcf	1800	123	1468		
186.crafty	1000	106	944		
197.parser	1800	181	992		
252.eon	1300	76.3	1704		
253.perlbmk	1800	120	1502		
254.gap	1100	83.0	1326		
255.vortex	1900	89.8	2115		
256.bzip2	1500	154	973		
300.twolf	3000	236	1272		

Hardware

CPU: Intel Xeon processor 7110N (2.5 GHz, 667 MHz bus)
CPU MHz: 2500
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1, 2, 4 chips
Parallel: No
Primary Cache: 12 K I micro-ops + 16 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 16 MB on chip per chip
Other Cache: N/A
Memory: 16 x 2048 MB ECC PC2-3200
Disk Subsystem: 73GB SAS 10K RPM
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005 (for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```

Bios Settings

Hardware Prefetch enabled
Memory Array set to High-Performance Memory Array