



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3650 (2.00 GHz Xeon E5335, 8MB L2 Cache)

SPECfp2000 = --

SPECfp_base2000 = 2020

SPEC license #: 11 Tested by: IBM Corporation Test date: Jan-2007 Hardware Avail: Feb-2007 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	55.1	2902			
171.swim	3100	120	2590			
172.mgrid	1800	138	1304			
173.applu	2100	135	1556			
177.mesa	1400	72.7	1925			
178.galgel	2900	59.8	4846			
179.art	2600	37.5	6936			
183.earthquake	1300	51.2	2541			
187.facerec	1900	96.2	1975			
188.amp	2200	150	1466			
189.lucas	2000	112	1786			
191.fma3d	2100	138	1520			
200.sixtrack	1100	137	801			
301.apsi	2600	217	1197			

Hardware

CPU: Intel Xeon processor E5335 (2.0 GHz, 1333 MHz bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1, 2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1024 MB ECC PC2-5300F
Disk Subsystem: 73GB SATA 15k RPM
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```