



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL380 G5 (2.66 GHz, Intel Xeon processor X5355)

SPECfp2000 = 2774

SPECfp_base2000 = 2531

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2007 Hardware Avail: Jan-2007 Software Avail: Nov-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	44.8	3568	44.8	3568	
171.swim	3100	114	2710	110	2816	
172.mgrid	1800	101	1775	79.6	2261	
173.applu	2100	114	1840	82.1	2558	
177.mesa	1400	50.4	2780	46.7	2997	
178.galgel	2900	46.3	6265	46.3	6265	
179.art	2600	24.9	10446	24.4	10673	
183.quake	1300	59.8	2175	49.4	2632	
187.facerec	1900	69.9	2719	50.6	3754	
188.amp	2200	111	1978	111	1978	
189.lucas	2000	97.5	2051	97.1	2060	
191.fma3d	2100	103	2030	103	2030	
200.sixtrack	1100	108	1020	108	1020	
301.apsi	2600	167	1555	158	1644	

Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 8 MB I+D on chip per chip (4 MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 16 GB (8x2 GB PC2-5300F CL5)
Disk Subsystem: 4x36 GB 10 K SAS
Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server version 10 for AMD64/EM64T Kernel 2.6.16.21-0.8-default
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20061101)
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20061101)
PathScale EKOPath(TM) Compiler Suite, Release 2.5
File System: ext2
System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (2.66 GHz, Intel Xeon processor X5355)

SPECfp2000 = 2774
SPECfp_base2000 = 2531

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jan-2007 | Hardware Avail: Jan-2007 | Software Avail: Nov-2006

Notes/Tuning Information (Continued)

```

177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art:    icc -fast -auto_ilp32 +FDO users=4
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
             -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
             users=4
188.ammp:   basepeak=1
189.lucas:  ifort -fast ONESTEP=yes
191.fma3d:  basepeak=1
200.sixtrack: basepeak=1
301.apsi:   pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t

```

BIOS Configuration Notes

Power Regulator set to Static High
Adjacent Sector Prefetch disabled

Other Configuration Notes

Taskset utility used to bind process to CPU(s)
"ulimit -s unlimited" set
Single processor kernel used