



# CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

## Intel(R) Corporation

Intel(R) DG965WH motherboard( 2.8 GHz, Intel(R) Pentium(TM) D processor 920)

SPECint2000 = 1424

SPECint\_base2000 = 1424

SPEC license #: 13 Tested by: Intel Corporation Test date: Oct-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	145	969	145	967	[Bar chart showing ratio]			
175.vpr	1400	143	980	141	990	[Bar chart showing ratio]			
176.gcc	1100	67.1	1639	67.1	1639	[Bar chart showing ratio]			
181.mcf	1800	95.8	1878	95.8	1878	[Bar chart showing ratio]			
186.crafty	1000	95.1	1051	95.8	1044	[Bar chart showing ratio]			
197.parser	1800	162	1112	161	1115	[Bar chart showing ratio]			
252.eon	1300	68.6	1894	68.9	1887	[Bar chart showing ratio]			
253.perlbmk	1800	106	1698	106	1695	[Bar chart showing ratio]			
254.gap	1100	68.2	1612	68.2	1612	[Bar chart showing ratio]			
255.vortex	1900	74.1	2565	74.1	2565	[Bar chart showing ratio]			
256.bzip2	1500	139	1078	139	1077	[Bar chart showing ratio]			
300.twolf	3000	211	1421	211	1421	[Bar chart showing ratio]			

### Hardware

CPU: Intel(R) Pentium(TM) D processor 920( 2.8 GHz, 800 MHz bus)  
CPU MHz: 2800  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12K micro-ops1 + 16KBD per core, on chip  
Secondary Cache: 2 MB(I+D) per core, on chip  
L3 Cache: None  
Other Cache: None  
Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)  
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)  
Other Hardware: SoundBlaster Live! PCI card

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_CC\_P\_9.1.020  
Microsoft Visual Studio 2005(for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard( 2.8 GHz, Intel(R) Pentium(TM) D processor 920)

SPECint2000 = 1424

SPECint\_base2000 = 1424

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO

300.twolf: -fast -O3 +FDO shlw32M.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 1/2007:

<http://www.intel.com/products/motherboard/DG965WH/index.htm>

The system bus runs at 1066 MHz