



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(2.67 GHz, Intel(R) Core(TM) 2 Duo processor E6700)

SPECfp2000 = 2776

SPECfp_base2000 = 2777

SPEC license #: 13 Tested by: Intel Corporation Test date: Oct-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	37.0	4328	37.0	4326	
171.swim	3100	99.6	3112	99.7	3111	
172.mgrid	1800	104	1739	103	1740	
173.applu	2100	93.3	2252	93.3	2252	
177.mesa	1400	55.8	2510	55.8	2510	
178.galgel	2900	45.1	6435	45.1	6435	
179.art	2600	27.9	9322	27.9	9322	
183.earthquake	1300	36.7	3546	36.4	3568	
187.facerec	1900	68.5	2774	68.7	2767	
188.ammmp	2200	113	1939	113	1952	
189.lucas	2000	72.1	2775	72.0	2777	
191.fma3d	2100	103	2043	103	2043	
200.sixtrack	1100	104	1062	105	1049	
301.apsi	2600	146	1775	146	1775	

Hardware

CPU: Intel(R) Core(TM) 2 Duo processor E6700(2.67 GHz, 1066 MHz bus)
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI + 32KBD per core, on chip
Secondary Cache: 4 MB(I+D) per chip, on chip (shared)
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: SoundBlaster Live! PCI card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Package IDs: W_CC_P_9.1.020 and W_FC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast +FDO shlw32M.lib
Base tuning for 179.art: -fast +FDO shlw32M.lib
Base tuning for 183.earthquake: -fast +FDO shlw32M.lib
Base tuning for 188.ammmp: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.earthquake: -QxP -Oa -Qrcd -Qipo +FDO shlw32M.lib
```



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(2.67 GHz, Intel(R) Core(TM) 2 Duo processor E6700)

SPECfp2000 = 2776

SPECfp_base2000 = 2777

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.ammf: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi: -fast +FDO

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 1/2007:

<http://www.intel.com/products/motherboard/DG965WH/index.htm>

The system bus runs at 1066 MHz